

Safety Data Sheet

according to UK REACH Regulation

Epoxy Resin L

Revision date: 13.03.2022

Product code: 100135

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Epoxy Resin L

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**Adhesives, sealants
Epoxy resin dispersions**1.3. Details of the supplier of the safety data sheet**

Company name: R&G Faserverbundwerkstoffe GmbH
 Street: Im Meißel 7 - 13
 Place: D-71111 Waldenbuch
 Post-office box: 1145
 D-71107 Waldenbuch
 Telephone: +49-7157-530460
 e-mail: info@r-g.de
 Contact person: Michael Groß
 e-mail: info@r-g.de
 Internet: www.r-g.de
 Responsible Department: Management

Telefax: +49-7157-530470

1.4. Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg
 Tel: +49 (0)761 19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:
 Skin corrosion/irritation: Skin Irrit. 2
 Serious eye damage/eye irritation: Eye Irrit. 2
 Respiratory or skin sensitisation: Skin Sens. 1
 Hazardous to the aquatic environment: Aquatic Chronic 2
 Hazard Statements:
 Causes skin irritation.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 Toxic to aquatic life with long lasting effects.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane
 1,6-bis(2,3-epoxypropoxy)hexane
 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Signal word: Warning**Pictograms:****Hazard statements**

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Entsorgung des Inhalts / des Behälters gemäß den örtlichen / regionalen / nationalen/internationalen Vorschriften
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Safety Data Sheet

according to UK REACH Regulation

Epoxy Resin L

Revision date: 13.03.2022

Product code: 100135

Page 2 of 10

Special labelling of certain mixtures

EUH205

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	GHS Classification	
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane	50 - 100 %
	216-823-5	01-2119456619-26
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411	
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane	10 - 25 %
	240-260-4	01-2119463471-41
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412	
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	10 - 25 %
	701-263-0	01-2119454392-40
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1675-54-3	216-823-5	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane	50 - 100 %
		dermal: LD50 = 23000 mg/kg; oral: LD50 = 15000 mg/kg	
16096-31-4	240-260-4	1,6-bis(2,3-epoxypropoxy)hexane	10 - 25 %
		dermal: LD50 = > 4900 mg/kg; oral: LD50 = 8500 mg/kg	
	701-263-0	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	10 - 25 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Take off immediately all contaminated clothing.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO₂), Extinguishing powder, Water spray jet.

Safety Data Sheet

according to UK REACH Regulation

Epoxy Resin L

Revision date: 13.03.2022

Product code: 100135

Page 3 of 10

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

The product itself does not burn. In case of fire may be liberated: Gases/vapours, toxic.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protection equipment. Evacuate area.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow to enter the soil or subsoil.

6.3. Methods and material for containment and cleaning up

Provide adequate ventilation. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

The usual precautions when handling chemicals must be observed.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep/Store only in original container. Provide for retaining containers, eg. floor pan without outflow.

Hints on joint storage

Store separately from foodstuffs.

Further information on storage conditions

Keep receptacles tightly sealed.

7.3. Specific end use(s)

Adhesives, sealants

Epoxy resin dispersions

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane			
Worker DNEL,		dermal		0,75 mg/kg bw/day
Worker DNEL,		inhalation		4,93 mg/m ³
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane			
Worker DNEL,		dermal		2,8 mg/kg bw/day
Worker DNEL,		inhalation		2,9 mg/m ³
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl]oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane			
Worker DNEL, long-term		dermal	systemic	104,15 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	29,39 mg/m ³

Safety Data Sheet

according to UK REACH Regulation

Epoxy Resin L

Revision date: 13.03.2022

Product code: 100135

Page 4 of 10

PNEC values

CAS No	Substance	
Environmental compartment		Value
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane	
Freshwater		0,006 mg/l
Marine water		0,001 mg/l
Freshwater sediment		0,341 mg/kg
Marine sediment		0,034 mg/kg
Secondary poisoning		11 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,065 mg/kg
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane	
Freshwater		0,0115 mg/l
Marine water		0,00115 mg/l
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl]oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane		
Freshwater		0,003 mg/l
Freshwater (intermittent releases)		0,025 mg/l
Marine water		0 mg/l
Freshwater sediment		0,294 mg/kg
Marine sediment		0,029 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,237 mg/kg

8.2. Exposure controls**Protective and hygiene measures**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable material: FKM (fluoro rubber), NBR (Nitrile rubber)

Thickness of the glove material: > 0,5mm

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. ABEK-P2

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	yellowish
Odour:	characteristic
Odour threshold:	not determined

pH-Value: not applicable

Changes in the physical state

Melting point/freezing point: not determined

Test method

Safety Data Sheet

according to UK REACH Regulation

Epoxy Resin L

Revision date: 13.03.2022

Product code: 100135

Page 5 of 10

Boiling point or initial boiling point and boiling range: 200 °C

Flash point: 150 °C

Flammability

Solid: not applicable

Gas: not applicable

Explosive properties

The product is not: Explosive.

Lower explosion limits: not determined

Upper explosion limits: not determined

Self-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: 1 hPa

(at 20 °C)

Density (at 23 °C): 1,1 g/cm³ ISO 2811-2

Water solubility: Immiscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Viscosity / dynamic: 875 mPa·s ISO 3219

(at 23 °C)

Relative vapour density: not determined

Evaporation rate: not determined

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

no decomposition when stored and handled properly

10.3. Possibility of hazardous reactions

reaction with strong oxidising agents Alkalis (alkalis). Acids

10.4. Conditions to avoid

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

10.5. Incompatible materials

Keep away from oxidising agents.

10.6. Hazardous decomposition products

no decomposition when stored and handled properly

In case of fire may be liberated: toxic and caustic gases and vapours

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

Epoxy Resin L

Revision date: 13.03.2022

Product code: 100135

Page 6 of 10

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane					
	oral	LD50 mg/kg	15000	rat		
	dermal	LD50 mg/kg	23000	rabbit		
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane					
	oral	LD50 mg/kg	8500	Rat	Manufacturer	
	dermal	LD50 mg/kg	> 4900	Rabbit	Manufacturer	
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane					
	oral	LD50 mg/kg	> 5000	Rat	Manufacturer	
	dermal	LD50 mg/kg	> 2000	Rat	Manufacturer	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Contains epoxy constituents. May produce an allergic reaction. May cause an allergic skin reaction. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane; 1,6-bis(2,3-epoxypropoxy)hexane; Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane					
	Acute fish toxicity	LC50	2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	11 mg/l	72 h	algae	
	Acute crustacea toxicity	EC50	1,8 mg/l	48 h	Daphnia magna	
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane					
	Acute fish toxicity	LC50	30 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Manufacturer
	Acute crustacea toxicity	EC50	67 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane					
	Acute fish toxicity	LC50	2,54 mg/l	96 h	Leuciscus idus (golden orfe)	Manufacturer
	Acute algae toxicity	ErC50	1,8 mg/l	72 h	Selenastrum capricornutum	Manufacturer
	Acute crustacea toxicity	EC50	2,55 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer

Safety Data Sheet

according to UK REACH Regulation

Epoxy Resin L

Revision date: 13.03.2022

Product code: 100135

Page 7 of 10

12.2. Persistence and degradability

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

12.3. Bioaccumulative potential

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

12.4. Mobility in soil

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

List of Wastes Code - used product

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Dispose of waste according to applicable legislation.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:**

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane; 1,6-bis(2,3-epoxypropoxy)hexane; Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

E

Other applicable information (land transport)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Inland waterways transport (ADN)**14.1. UN number:**

UN 3082

Safety Data Sheet

according to UK REACH Regulation

Epoxy Resin L

Revision date: 13.03.2022

Product code: 100135

Page 8 of 10

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane; 1,6-bis(2,3-epoxypropoxy)hexane; Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Limited quantity:

5 L

Other applicable information (inland waterways transport)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Marine transport (IMDG)**14.1. UN number:**

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane; hexanediol diglycidyl ether)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Marine pollutant:

Ja

Limited quantity:

5 L

Excepted quantity:

E 1

EmS:

F-A, S-F

Other applicable information (marine transport)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number:**

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane; hexanediol diglycidyl ether)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Limited quantity Passenger:

5 L

Excepted quantity:

E 1

Other applicable information (air transport)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

Yes



Danger releasing substance:

bis[4(2,3-epoxypropoxy)phenyl]propane

14.6. Special precautions for user

No information available.

Safety Data Sheet

according to UK REACH Regulation

Epoxy Resin L

Revision date: 13.03.2022

Product code: 100135

Page 9 of 10

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to 2012/18/EU
(SEVESO III):

E2 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,14.

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord

européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Safety Data Sheet

according to UK REACH Regulation

Epoxy Resin L

Revision date: 13.03.2022

Product code: 100135

Page 10 of 10

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)