

**Safety Data Sheet**

according to UK REACH Regulation

**Epoxy Casting Resin (water-clear)**

Revision date: 05.01.2023

Product code: 107106

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Epoxy Casting Resin (water-clear)

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Epoxy resin binder

**1.3. Details of the supplier of the safety data sheet**

Company name:	R&G Faserverbundwerkstoffe GmbH	
Street:	Im Meißel 7 - 13	
Place:	D-71111 Waldenbuch	
Post-office box:	1145	
	D-71107 Waldenbuch	
Telephone:	+49-7157-530460	Telefax: +49-7157-530470
e-mail:	info@r-g.de	
Contact person:	Michael Groß	
e-mail:	info@r-g.de	
Internet:	www.r-g.de	
Responsible Department:	Management	

**1.4. Emergency telephone number:** Vergiftungs-Informations-Zentrale Freiburg  
Tel: +49 (0)761 19240

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

Harmful to aquatic life with long lasting effects.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane

1,6-bis(2,3-epoxypropoxy)hexane

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-((2-[4-

(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

**Signal word:** Warning**Pictograms:****Hazard statements**

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

**Safety Data Sheet**

according to UK REACH Regulation

**Epoxy Casting Resin (water-clear)**

Revision date: 05.01.2023

Product code: 107106

Page 2 of 10

**Special labelling of certain mixtures**

EUH205

Contains epoxy constituents. May produce an allergic reaction.

**2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	GHS Classification	
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane	50 - 100 %
	216-823-5	01-2119456619-26
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411	
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane	10 - 25 %
	240-260-4	01-2119463471-41
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412	
	Reaction mass of 2,2'-[methylenabis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenabis(2,1-phenyleneoxymethylene)]dioxirane	10 - 25 %
	701-263-0	01-2119454392-40
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1675-54-3	216-823-5	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane	50 - 100 %
		dermal: LD50 = 23000 mg/kg; oral: LD50 = 15000 mg/kg	
16096-31-4	240-260-4	1,6-bis(2,3-epoxypropoxy)hexane	10 - 25 %
		dermal: LD50 = > 4900 mg/kg; oral: LD50 = 8500 mg/kg	
	701-263-0	Reaction mass of 2,2'-[methylenabis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenabis(2,1-phenyleneoxymethylene)]dioxirane	10 - 25 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Take off immediately all contaminated clothing.

**After inhalation**

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

**After contact with skin**

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

Seek medical advice immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water spray jet.

**Safety Data Sheet**

according to UK REACH Regulation

**Epoxy Casting Resin (water-clear)**

Revision date: 05.01.2023

Product code: 107106

Page 3 of 10

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

The product itself does not burn. In case of fire may be liberated: Gases/vapours, toxic.

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

**Additional information**

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protection equipment. Evacuate area.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

Do not allow to enter the soil or subsoil.

**6.3. Methods and material for containment and cleaning up**

Provide adequate ventilation. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

The usual precautions when handling chemicals must be observed.

**Advice on protection against fire and explosion**

No special fire protection measures are necessary.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep/Store only in original container. Provide for retaining containers, eg. floor pan without outflow.

**Hints on joint storage**

Store separately from foodstuffs.

**Further information on storage conditions**

Keep receptacles tightly sealed.

**7.3. Specific end use(s)**

Adhesives, sealants

Epoxy resin dispersions

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane			
Worker DNEL,		dermal		8,33 mg/kg bw/day
Worker DNEL,		inhalation		12,25 mg/m <sup>3</sup>
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane			
Worker DNEL,		dermal		2,8 mg/kg bw/day
Worker DNEL,		inhalation		2,9 mg/m <sup>3</sup>
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl]oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane			
Worker DNEL, long-term		dermal	systemic	104,15 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	29,39 mg/m <sup>3</sup>

**Safety Data Sheet**

according to UK REACH Regulation

**Epoxy Casting Resin (water-clear)**

Revision date: 05.01.2023

Product code: 107106

Page 4 of 10

**PNEC values**

CAS No	Substance	
Environmental compartment		Value
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane	
Freshwater		0,006 mg/l
Marine water		0,001 mg/l
Freshwater sediment		0,341 mg/kg
Marine sediment		0,034 mg/kg
Secondary poisoning		11 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,065 mg/kg
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane	
Freshwater		0,0115 mg/l
Marine water		0,00115 mg/l
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl]oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane		
Freshwater		0,003 mg/l
Freshwater (intermittent releases)		0,025 mg/l
Marine water		0 mg/l
Freshwater sediment		0,294 mg/kg
Marine sediment		0,029 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,237 mg/kg

**Additional advice on limit values**

The product does not contain any relevant quantities of substances with limit values that require monitoring at the workplace.

**8.2. Exposure controls****Protective and hygiene measures**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Eye/face protection**

Suitable eye protection: goggles.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable material: FKM (fluoro rubber), NBR (Nitrile rubber)

Thickness of the glove material: > 0,5mm

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection. ABEK-P2

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	yellowish
Odour:	characteristic
Odour threshold:	not determined

**Test method**

**Safety Data Sheet**

according to UK REACH Regulation

**Epoxy Casting Resin (water-clear)**

Revision date: 05.01.2023

Product code: 107106

Page 5 of 10

pH-Value: not applicable

**Changes in the physical state**

Melting point/freezing point: not determined

Boiling point or initial boiling point and boiling range: 200 °C

Flash point: 150 °C

**Flammability**

Solid: not applicable

Gas: not applicable

**Explosive properties**

The product is not: Explosive.

Lower explosion limits: not determined

Upper explosion limits: not determined

**Self-ignition temperature**

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties**

Not oxidising.

Vapour pressure: 1 hPa

(at 20 °C)

Density (at 23 °C): 1,1 g/cm<sup>3</sup> ISO 2811-2

Water solubility: Immiscible

**Solubility in other solvents**

not determined

Partition coefficient n-octanol/water: not determined

Viscosity / dynamic: 875 mPa·s ISO 3219

(at 23 °C)

Relative vapour density: not determined

Evaporation rate: not determined

**9.2. Other information**

No information available.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

no decomposition when stored and handled properly

**10.3. Possibility of hazardous reactions**

reaction with strong oxidising agents Alkalis (alkalis). Acids

**10.4. Conditions to avoid**

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

**10.5. Incompatible materials**

Keep away from oxidising agents.

**10.6. Hazardous decomposition products**

no decomposition when stored and handled properly

In case of fire may be liberated: toxic and caustic gases and vapours

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to UK REACH Regulation

**Epoxy Casting Resin (water-clear)**

Revision date: 05.01.2023

Product code: 107106

Page 6 of 10

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane					
	oral	LD50 mg/kg	15000	rat		
	dermal	LD50 mg/kg	23000	rabbit		
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane					
	oral	LD50 mg/kg	8500	Rat	Manufacturer	
	dermal	LD50 mg/kg	> 4900	Rabbit	Manufacturer	
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane					
	oral	LD50 mg/kg	> 5000	Rat	Manufacturer	
	dermal	LD50 mg/kg	> 2000	Rat	Manufacturer	

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

**Sensitising effects**

Contains epoxy constituents. May produce an allergic reaction. May cause an allergic skin reaction. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane; 1,6-bis(2,3-epoxypropoxy)hexane; Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information****12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane					
	Acute fish toxicity	LC50	2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	11 mg/l	72 h	algae	
	Acute crustacea toxicity	EC50	1,8 mg/l	48 h	Daphnia magna	
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane					
	Acute fish toxicity	LC50	30 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Manufacturer
	Acute crustacea toxicity	EC50	67 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane					
	Acute fish toxicity	LC50	2,54 mg/l	96 h	Leuciscus idus (golden orfe)	Manufacturer
	Acute algae toxicity	ErC50	1,8 mg/l	72 h	Selenastrum capricornutum	Manufacturer
	Acute crustacea toxicity	EC50	2,55 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer

**Safety Data Sheet**

according to UK REACH Regulation

**Epoxy Casting Resin (water-clear)**

Revision date: 05.01.2023

Product code: 107106

Page 7 of 10

**12.2. Persistence and degradability**

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

**12.3. Bioaccumulative potential**

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

**12.4. Mobility in soil**

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

**12.5. Results of PBT and vPvB assessment**

not applicable

**12.6. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

**List of Wastes Code - used product**

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

Dispose of waste according to applicable legislation.

**SECTION 14: Transport information****Land transport (ADR/RID)****14.1. UN number:**

UN 3082

**14.2. UN proper shipping name:**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane; 1,6-bis(2,3-epoxypropoxy)hexane; Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)

**14.3. Transport hazard class(es):**

9

**14.4. Packing group:**

III

Hazard label:

9



Classification code:

M6

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

E

**Other applicable information (land transport)**

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

**Inland waterways transport (ADN)****14.1. UN number:**

UN 3082

**Safety Data Sheet**

according to UK REACH Regulation

**Epoxy Casting Resin (water-clear)**

Revision date: 05.01.2023

Product code: 107106

Page 8 of 10

**14.2. UN proper shipping name:**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane; 1,6-bis(2,3-epoxypropoxy)hexane; Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)

**14.3. Transport hazard class(es):**

9

**14.4. Packing group:**

III

Hazard label:

9



Classification code:

M6

Limited quantity:

5 L

**Other applicable information (inland waterways transport)**

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

**Marine transport (IMDG)****14.1. UN number:**

UN 3082

**14.2. UN proper shipping name:**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane; hexanediol diglycidyl ether)

**14.3. Transport hazard class(es):**

9

**14.4. Packing group:**

III

Hazard label:

9



Marine pollutant:

Ja

Limited quantity:

5 L

Excepted quantity:

E 1

EmS:

F-A, S-F

**Other applicable information (marine transport)**

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number:**

UN 3082

**14.2. UN proper shipping name:**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane; hexanediol diglycidyl ether)

**14.3. Transport hazard class(es):**

9

**14.4. Packing group:**

III

Hazard label:

9



Limited quantity Passenger:

5 L

Excepted quantity:

E 1

**Other applicable information (air transport)**

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:

Yes



Danger releasing substance:

bis[4(2,3-epoxypropoxy)phenyl]propane

**14.6. Special precautions for user**

No information available.



**Safety Data Sheet**

according to UK REACH Regulation

**Epoxy Casting Resin (water-clear)**

Revision date: 05.01.2023

Product code: 107106

Page 9 of 10

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to 2012/18/EU  
(SEVESO III):

E2 Hazardous to the Aquatic Environment

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method
Aquatic Chronic 3; H412	

**Safety Data Sheet**

according to UK REACH Regulation

**Epoxy Casting Resin (water-clear)**

Revision date: 05.01.2023

Product code: 107106

Page 10 of 10

**Relevant H and EUH statements (number and full text)**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*