

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mould resin P

Revision date: 21.11.2019

Product code: 115160

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Mould resin P

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet**

Company name:	R&G Faserverbundwerkstoffe GmbH	
	Composite Technology	
Street:	Im Meißel 7 - 13	
Place:	D-71111 Waldenbuch	
Post-office box:	1145	
	D-71107 Waldenbuch	
Telephone:	+49 (0)7157 5304-60	Telefax: +49 (0)7157 5304-70
e-mail:	info@r-g.de	
Internet:	www.r-g.de	
Responsible Department:	Management	

1.4. Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg
Tel: +49 (0)761 19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Acute toxicity: Acute Tox. 4

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes serious eye irritation.


Causes skin irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

reaction product: bisphenol-A-(epichlorhydrin), (number average molecular weight < 700),

Signal word: Warning**Pictograms:****Hazard statements**

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mould resin P

Revision date: 21.11.2019

Product code: 115160

Page 2 of 8

Precautionary statements

P351 Rinse cautiously with water for several minutes.
 P338 Remove contact lenses, if present and easy to do. Continue rinsing.
 P305 IF IN EYES:
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin), (number average molecular weight < 700),			1 - < 50 %
	500-033-5	603-074-00-8		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
9003-36-5	epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin)			1 - < 20 %
	500-006-8	603-074-00-8	01-2119454392-40	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane			1 - < 10 %
	240-260-4		01-2119463471-41	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

never give an unconscious person things thru the mouth

After inhalation

Provide fresh air. Consult physician. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Consult physician if problems persist. Remove contaminated, saturated clothing immediately.

After contact with eyes

After contact with eye rinse immediately with lot of water at least 5 minutes with open eyelid. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

SECTION 11: Toxicological information

SECTION 4: First aid measures

After inhaling vapours, first symptoms of poisoning may develop hours later, so always consult a doctor.

SECTION 5: Firefighting measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mould resin P

Revision date: 21.11.2019

Product code: 115160

Page 3 of 8

5.1. Extinguishing media**Suitable extinguishing media**

Carbon dioxide (CO₂). Extinguishing powder. Water spray. Fight major fires with a water spray jet or alcohol-resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: , toxic gases, Chlorhydric gas (HCl).

5.3. Advice for firefighters

Wear a protective full body suit. Wear breathing apparatus without recirculating air and suitable protective clothing.

Additional information

Fire residue and contaminated firefighting water must be disposed of in accordance with government regulations.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation of the storage area. Avoid contact with skin. Avoid contact with eyes.

6.2. Environmental precautions

Contain escaping liquid with suitable material (e.g. soil).

Do not let the product enter the groundwater, open water, or the sewerage system.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Formation of toxic gases is possible during heating or in case of fire.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate room ventilation, if necessary with vapour extraction at the workplace. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. When using do not eat, drink, smoke or sneeze.

Further information on handling

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Employ reliable measures to prevent the product from entering the soil.

Further information on storage conditions

Keep in well sealed receptacles at a cool, dry location.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation/vapour extraction at the workplace.

Protective and hygiene measures

The usual precautions when handling chemicals must be observed.

after work and before breaks for thorough skin cleansing. Keep away from food, drink and animal feeding

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mould resin P

Revision date: 21.11.2019

Product code: 115160

Page 4 of 8

stuffs. Contaminated work clothing should not be allowed out of the workplace.

Eye/face protection

Protective goggles (EN 166)

Hand protection

Only chemicals - protective gloves with CE-labeling of category 3 use. (EN374)

Skin protection

Wear protective clothing.

Respiratory protection

Not necessary when the room is well ventilated.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid Paste
Colour:	black
Odour:	weak characteristic

Test method**Changes in the physical state**

Flash point: > 150 °C

Vapour pressure: <0,1 hPa
(at 20 °C)Density (at 20 °C): 1,26-1,34 g/cm³ DIN 53217

Water solubility: insoluble in water

SECTION 10: Stability and reactivity**10.1. Reactivity**

The product has not been tested.

10.2. Chemical stability

Stabile under the specified storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions at a correct storage and handling.

10.4. Conditions to avoidSECTION 7: Handling and storage
none known**10.5. Incompatible materials**SECTION 7: Handling and storage
Polymerisation : alkalis and numerous organic substance categories like alcohols and amines**10.6. Hazardous decomposition products**

no decomposition when stored and handled properly

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**oral LD50: 11400 mg/kg rat
LD50: >2000 mg/kg rabbit**ATEmix calculated**

ATE (oral) 2000,0 mg/kg; ATE (dermal) 1270,0 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mould resin P

Revision date: 21.11.2019

Product code: 115160

Page 5 of 8

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin), (number average molecular weight < 700),					
	oral	LD50 2000 mg/kg	Mouse			
	dermal	LD50 1270 mg/kg	Mouse			
9003-36-5	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-F-(epichlorhydrin)					
	oral	LD50 > 2000 mg/kg	Rat			
	dermal	LD50 > 2000 mg/kg	Rabbit			
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane					
	oral	LD50 3010 mg/kg	Rat	OECD 401		
	dermal	LD50 > 2000 mg/kg	Rat	OECD 402		

Irritation and corrosivity

Irritation to skin, eyes, and mucous membranes.

Sensitising effects

May cause sensitization by inhalation and skin contact.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin), (number average molecular weight < 700),					
	Acute fish toxicity	LC50 1,3 mg/l	96 h			
	Acute algae toxicity	ErC50 220 mg/l	96 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 2,8 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	(3,6 mg/l)		Leuciscus idus (golden orfe)		
9003-36-5	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-F-(epichlorhydrin)					
	Acute fish toxicity	LC50 2,54 mg/l	96 h			
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane					
	Acute fish toxicity	LC50 30 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203	
	Acute crustacea toxicity	EC50 39 - 57 mg/l	48 h	Daphnia magna	OECD 202	

12.2. Persistence and degradability

Biological degradation: Product is biodegradable with difficulty.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mould resin P

Revision date: 21.11.2019

Product code: 115160

Page 6 of 8

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
9003-36-5	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-F-(epichlorhydrin)			
	OECD 301B	16%	28	Manufacturer
	Not readily biodegradable (according to OECD criteria)			
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane			
	OECD 301D	47%	28	Manufacturer
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

BCF

CAS No	Chemical name	BCF	Species	Source
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane	3,57		

Further information

Do not let the product enter the groundwater, open water, or the sewerage system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9



Classification code:	M6
Special Provisions:	274 335 601
Limited quantity:	5 L
Transport category:	3
Hazard No:	90
Tunnel restriction code:	E

Other applicable information (land transport)

E1

Inland waterways transport (ADN)

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9

Safety Data Sheet


according to Regulation (EC) No 1907/2006

Mould resin P

Revision date: 21.11.2019

Product code: 115160

Page 7 of 8



Classification code: M6
 Special Provisions: 274 335 601
 Limited quantity: 5 L

Other applicable information (inland waterways transport)

E1

Marine transport (IMDG)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Marine pollutant: Ja
 Special Provisions: 274, 335
 Limited quantity: 5 L
 EmS: F-A, S-F

Other applicable information (marine transport)

E1

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Special Provisions: A97 A158
 Limited quantity Passenger: 30 kg G
 IATA-packing instructions - Passenger: 964
 IATA-max. quantity - Passenger: 450 L
 IATA-packing instructions - Cargo: 964
 IATA-max. quantity - Cargo: 450 L

Other applicable information (air transport)

E1

Passenger-LQ: Y964

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mould resin P

Revision date: 21.11.2019

Product code: 115160

Page 8 of 8

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 8 %

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)