

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Universal Colour Paste**

Revision date: 26.02.2019

Product code: 132100

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Universal Colour Paste

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.3. Details of the supplier of the safety data sheet**

|                         |                                 |                          |
|-------------------------|---------------------------------|--------------------------|
| Company name:           | R&G Faserverbundwerkstoffe GmbH |                          |
| Street:                 | Im Meißel 7 - 13                |                          |
| Place:                  | D-71111 Waldenbuch              |                          |
| Post-office box:        | 1145                            |                          |
|                         | D-71107 Waldenbuch              |                          |
| Telephone:              | +49-7157-530460                 | Telefax: +49-7157-530470 |
| e-mail:                 | info@r-g.de                     |                          |
| Internet:               | www.r-g.de                      |                          |
| Responsible Department: | Management                      |                          |

**1.4. Emergency telephone number:** Vergiftungs-Informations-Zentrale Freiburg  
Tel: +49 (0)761 19240

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:  
Respiratory or skin sensitisation: Skin Sens. 1  
Hazard Statements:  
May cause an allergic skin reaction.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

Fettsäure, C18-ungesät., Trimere, Vbgn.mit Oleylamin  
Fettsäure, Talloel, Verbindung mit Oleylamin  
[N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyanintrimethylaminato(2-)-N29,N

**Signal word:** Warning

**Pictograms:****Hazard statements**

H317 May cause an allergic skin reaction.

**Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of Water and soap.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.

**2.3. Other hazards**

No information available.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Universal Colour Paste

Revision date: 26.02.2019

Product code: 132100

Page 2 of 8

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous components

| CAS No      | Chemical name                                                                 |          |                  | Quantity     |
|-------------|-------------------------------------------------------------------------------|----------|------------------|--------------|
|             | EC No                                                                         | Index No | REACH No         |              |
|             | GHS Classification                                                            |          |                  |              |
| 123-86-4    | n-butyl acetate                                                               |          |                  | 2,5 < 5 %    |
|             | 204-658-1                                                                     |          | 01-2119485493-29 |              |
|             | Flam. Liq. 3, STOT SE 3; H226 H336                                            |          |                  |              |
| 147900-93-4 | Fettsäure, C18-ungesät., Trimere, Vbgn.mit Oleylamin                          |          |                  | 0,25 < 0,5 % |
|             | 604-612-4                                                                     |          | 01-2119971821-33 |              |
|             | Acute Tox. 4, Skin Sens. 1, STOT RE 2, Aquatic Chronic 2; H302 H317 H373 H411 |          |                  |              |
| 85711-55-3  | Fettsäure, Talloel, Verbindung mit Oleylamin                                  |          |                  | 0,25 < 0,5 % |
|             | 288-315-1                                                                     |          | 01-2119974148-28 |              |
|             | Eye Dam. 1, Skin Sens. 1A, STOT RE 2; H318 H317 H373                          |          |                  |              |
| 28654-73-1  | [N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyanintrimethylaminato(2-)-N29,N  |          |                  | 0,1 < 0,25 % |
|             | 249-125-4                                                                     |          | 01-2119971074-38 |              |
|             | Skin Sens. 1B; H317                                                           |          |                  |              |

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use for cleaning purposes.: Solvent/Thinner.

#### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Universal Colour Paste

Revision date: 26.02.2019

Product code: 132100

Page 3 of 8

### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide, Powder, Water spray jet.

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: , Gases/vapours, harmful

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area. Do not breathe vapour.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Do not use for cleaning purposes.: Solvent/Thinner.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Only use the material in places where open light, fire and other flammable sources can be kept away. Use explosion-proof electrical equipment. Take precautionary measures against static discharges. Provide earthing of containers, equipment, pumps and ventilation facilities. Use only antistatically equipped (spark-free) tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Suitable floor material: conductive Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer). When using do not eat, drink or smoke. Never use pressure to empty container.

#### Advice on protection against fire and explosion

Vapours are heavier than air. Vapours can form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Never use pressure to empty container. Store in a place accessible by authorized persons only. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

#### Hints on joint storage

Keep away from: Strong acid, Strong alkali, Oxidizing agents.

#### Further information on storage conditions

Notice the directions for use on the label. Store in a well-ventilated place. Store in a dry place. Recommended storage temperature: 5 25 °C. Protect against direct sunlight. Remove all sources of ignition.

### 7.3. Specific end use(s)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Universal Colour Paste**

Revision date: 26.02.2019

Product code: 132100

Page 4 of 8

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

| CAS No   | Substance     | ppm | mg/m <sup>3</sup> | fibres/ml | Category      | Origin |
|----------|---------------|-----|-------------------|-----------|---------------|--------|
| 123-86-4 | Butyl acetate | 150 | 724               |           | TWA (8 h)     | WEL    |
|          |               | 200 | 966               |           | STEL (15 min) | WEL    |

**8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations. In case of inadequate ventilation wear respiratory protection.

**Protective and hygiene measures**

After contact with skin, wash immediately with plenty of water and soap.

**Eye/face protection**

Tightly sealed safety glasses.

**Hand protection**

Wear suitable gloves. (DIN EN 374)

Thickness of glove material: > 0,4 mm

penetration time (maximum wearing period): > 480 min

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protect skin by using skin protective cream. Use protective skin cream before handling the product.

**Skin protection**

Wear suitable protective clothing. (antistatic) Natural fibres (e.g. cotton), heat-resistant synthetic fibres.

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

|                 |                |                |
|-----------------|----------------|----------------|
| Physical state: | Liquid         |                |
| Colour:         | various        |                |
| Odour:          | characteristic |                |
| pH-Value:       |                | not determined |

**Changes in the physical state**

|                                          |  |                |
|------------------------------------------|--|----------------|
| Melting point:                           |  | not applicable |
| Initial boiling point and boiling range: |  | 124 °C         |

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Universal Colour Paste**

Revision date: 26.02.2019

Product code: 132100

Page 5 of 8

Flash point: not applicable

**Flammability**

Solid: not determined

Gas: not applicable

**Explosive properties**

not applicable

Lower explosion limits: 1,2 vol. %

Upper explosion limits: 7,5 vol. %

Ignition temperature: 390 °C

**Auto-ignition temperature**

Solid: not determined

Gas: not applicable

Decomposition temperature: not applicable

**Oxidizing properties**

not applicable

Vapour pressure: 0,38 hPa

(at 20 °C)

Density (at 20 °C): 1,18 g/cm<sup>3</sup>

Water solubility: practically insoluble

**Solubility in other solvents**

not determined

Partition coefficient: not determined

Viscosity / dynamic: Paste

Viscosity / kinematic: Paste

Vapour density: not applicable

Evaporation rate: not applicable

Solvent content: : 4 Wt %

Water: 0 Wt %

**9.2. Other information**

Solid content: 95,65 %

Odour threshold: not determined

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Exothermic reaction with: Strong acid, Strong alkali, Oxidizing agents.

**10.5. Incompatible materials**

Strong acid, Strong alkali, Oxidizing agents.

**10.6. Hazardous decomposition products**Hazardous decomposition products: Carbon monoxide, Carbon dioxide (CO<sub>2</sub>), , Nitrogen oxides (NO<sub>x</sub>).**SECTION 11: Toxicological information**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Universal Colour Paste**

Revision date: 26.02.2019

Product code: 132100

Page 6 of 8

**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

| CAS No      | Chemical name                                        |               |         |        |        |
|-------------|------------------------------------------------------|---------------|---------|--------|--------|
|             | Exposure route                                       | Dose          | Species | Source | Method |
| 147900-93-4 | Fettsäure, C18-ungesät., Trimere, Vbgn.mit Oleylamin |               |         |        |        |
|             | oral                                                 | ATE 500 mg/kg |         |        |        |

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

May cause an allergic skin reaction. (Fettsäure, C18-ungesät., Trimere, Vbgn.mit Oleylamin; Fettsäure, Talloel, Verbindung mit Oleylamin; [N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyanintrimethylaminato(2-)-N29,N)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

Overall Assessment on CMR properties: This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience****Other observations**

Irritation to respiratory tract , Causes damage to organs.: liver, kidneys, central nervous system. The following symptoms may occur: Headache, Dizziness, , , Drowsiness, Unconsciousness.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Following eye contact: Irritant

**SECTION 12: Ecological information****12.1. Toxicity**

No data available

**12.2. Persistence and degradability**

No data available

**12.3. Bioaccumulative potential**

No data available

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Universal Colour Paste**

Revision date: 26.02.2019

Product code: 132100

Page 7 of 8

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**Waste disposal number of waste from residues/unused products**

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Inland waterways transport (ADN)**

**14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Marine transport (IMDG)**

**14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Keep container tightly closed.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Universal Colour Paste**

Revision date: 26.02.2019

Product code: 132100

Page 8 of 8

**EU regulatory information**

2010/75/EU (VOC): 51 g/L

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - clearly water contaminating

**Additional information**

Berufsgenossenschaftliche Regeln (BGR)

BGR 190

BGR 192

BGR 195

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Relevant H and EUH statements (number and full text)**

H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.

**Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*