

Safety Data Sheet

according to UK REACH Regulation

Universal Colour Paste Silver grey (RAL 7001)

Revision date: 08.03.2023

Product code: 132125X

Page 1 of 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Universal Colour Paste Silver grey (RAL 7001)

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

For the pigmentation of EP, UP or PU resins and for condensation-curing silicon moulding compounds (cannot be used for addition-curing silicone moulding compounds).

1.3. Details of the supplier of the safety data sheet

Company name: R&G Faserverbundwerkstoffe GmbH

Street: Im Meißel 7 - 13

Place: D-71111 Waldenbuch

Post-office box: 1145

D-71107 Waldenbuch

Telephone: +49-7157-530460

Telefax: +49-7157-530470

e-mail: info@r-g.de

Contact person: Michael Groß

e-mail: info@r-g.de

Internet: www.r-g.de

Responsible Department: Management

1.4. Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg
Tel: +49 (0)761 19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements**GB CLP Regulation****Special labelling of certain mixtures**

EUH208 Contains Fettsäure, Talloel, Verbindung mit Oleylamin. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
77-99-6	Propyldyntrimethanole	< 1 %
	201-074-9	
	01-2119486799-10	
	Repr. 2; H361fd	
85711-55-3	Fettsäure, Talloel, Verbindung mit Oleylamin	< 0,1 %
	288-315-1	
	01-2119974148-28	
	Eye Dam. 1, Skin Sens. 1A, STOT RE 2; H318 H317 H373	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice.

Safety Data Sheet

according to UK REACH Regulation

Universal Colour Paste Silver grey (RAL 7001)

Revision date: 08.03.2023

Product code: 132125X

Page 2 of 5

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use for cleaning purposes.: Solvent/Thinner.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting. Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide, Powder, Water spray.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. Hazardous decomposition products: carbon black. Health hazard. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe dust/fume/gas/mist/vapours/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away.

Use explosion-proof electrical equipment. Filling and transfer: Take precautionary measures against static discharges. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes, and clothing. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink, smoke, sniff. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

Solvent vapours are heavier than air, spread on the ground and form explosive mixtures with air mixtures.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV)

Hints on joint storage

Keep away from: Strong acid, Strong alkali, Oxidizing agents.

Further information on storage conditions

Follow the instructions for use on the label. Keep container tightly closed and dry in a cool, well-ventilated place. Protect

Safety Data Sheet

according to UK REACH Regulation

Universal Colour Paste Silver grey (RAL 7001)

Revision date: 08.03.2023

Product code: 132125X

Page 3 of 5

from heat and direct sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

7.3. Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Additional advice on limit values**

To date, no national critical limit values exist.

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves. Replace when worn! The design of chemical protective gloves must be selected specifically for the workplace, depending on the concentration and quantity of the hazardous substance. It is recommended to clarify the chemical resistance of the above mentioned protective gloves for special applications with the glove manufacturer. The wearing time limits according to the manufacturer's specifications must be observed.

Suitable material: FKM (fluororubber). Breakthrough time: >480 min.

Protect skin by using skin protective cream. Use protective skin cream before handling the product.

Skin protection

Wear anti-static footwear and clothing (antistatic) Natural fibres (e.g. cotton), heat-resistant synthetic fibres.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values. Use suitable breathing apparatus.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	silver grey (RAL 7001)
Odour:	like: Solvents

Changes in the physical state**Explosive properties**

not applicable

Density (at 20 °C): 2,03 g/cm³

Evaporation rate: not applicable

Solvent separation test: <3 % (land transport (ADR/RID))

Solvent content: 0,30%

9.2. Other information

Solid content: 99,70 %

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Strong acid, Strong alkali, Oxidizing agents.

10.6. Hazardous decomposition productsNitrogen oxides (NOx), carbon black, Carbon dioxide (CO₂), Carbon monoxide.**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

Safety Data Sheet

according to UK REACH Regulation

Universal Colour Paste Silver grey (RAL 7001)

Revision date: 08.03.2023

Product code: 132125X

Page 4 of 5

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Fettsäure, Talloel, Verbindung mit Oleylamin. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Observations relevant to classification

Following inhalation:

Possible adverse effects on humans and possible symptoms: May cause respiratory irritation. May cause damage to the liver if inhaled. May cause damage to the kidneys if inhaled. Central nervous system depression.

Following eye contact:

Irritating to eyes. (Reversible)

After skin contact:

May be absorbed through the skin. Frequent and prolonged skin contact may cause skin irritation. Has a degreasing effect on the skin.

after ingestion:

Symptoms: Nausea, vomiting, gastrointestinal complaints

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

SECTION 12: Ecological information**12.2. Persistence and degradability**

No data available

12.3. Bioaccumulative potential

No data available

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains.

Observe regulations when disposing.

Contaminated packaging

Non-contaminated packages may be recycled.

Observe regulations when disposing.

SECTION 14: Transport information**Land transport (ADR/RID)****14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.**Other applicable information (land transport)**

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.**Other applicable information (inland waterways transport)**

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.**Other applicable information (marine transport)**

No dangerous good in sense of this transport regulation.

Safety Data Sheet

according to UK REACH Regulation

Universal Colour Paste Silver grey (RAL 7001)

Revision date: 08.03.2023

Product code: 132125X

Page 5 of 5

Air transport (ICAO-TI/IATA-DGR)**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.**Other applicable information (air transport)**

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 0,301 % (6,095 g/l)

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 EUH208 Contains Fettsäure, Talloel, Verbindung mit Oleylamin. May produce an allergic reaction.
 EUH210 Safety data sheet available on request.
 EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)