

according to Regulation (EC) No 1907/2006

### MD-Mix Stahl/Metall, Alu, Wasser, Kupfer

Revision date: 17.04.2023 Product code: MIX Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

MD-Mix Stahl/Metall, Alu, Wasser, Kupfer

#### Further trade names

MIX.S MD-Mix Stahl/Metall MIX.A MD-Mix Aluminium MIX.W MD-Mix Wasser MIX.K MD-Mix Kupfer

UFI: J1PT-79T8-R004-G3JW

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Adhesives and sealants

### 1.3. Details of the supplier of the safety data sheet

Company name: Marston-Domsel GmbH Street: Bergheimer Str. 15 Place: 53909 Zülpich

Telephone: +49 (0) 22 52 94 15 - 0 Telefax: +49 (0) 22 52 17 44

e-mail: info@marston-domsel.de
Contact person: Qualitäsmanagement
e-mail: QM@marston-domsel.de
Internet: www.marston-domsel.de

1.4. Emergency telephone Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Regulation (EC) No 1272/2008

Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide

Signal word: Warning

Pictograms:



### **Hazard statements**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

## MD-Mix Stahl/Metall, Alu, Wasser, Kupfer

Revision date: 17.04.2023 Product code: MIX Page 2 of 10

#### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

### Special labelling of certain mixtures

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

### 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Resulting from the use of the product: reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) Contains epoxy constituents. May produce an allergic reaction.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **Hazardous components**

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No	1272/2008)				
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane					
	216-823-5	603-073-00-2	01-2119456619-26			
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens	s. 1, Aquatic Chronic 2; H315 H319	H317 H411			
72244-98-5	Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide					
	701-196-7		01-2120118957-46			
	Skin Sens. 1B, Aquatic Chronic 3	; H317 H412				
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol					
	202-013-9	603-069-00-0	01-2119560597-27			
	Acute Tox. 4, Skin Irrit. 2, Eye Irri	t. 2; H302 H315 H319				
13463-67-7	titanium dioxide					
	236-675-5		01-2119489379-17			
		·		· ·		

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
1675-54-3	216-823-5	bis-[4-(2,3-epoxipropoxi)phenyl]propane	10 - < 20 %
	Skin Irrit. 2; H3	315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	
72244-98-5	701-196-7	Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide	10 - < 20 %
	dermal: LD50	0 = > 10200 mg/kg; oral: LD50 = 2600 mg/kg	
90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	< 5 %
	oral: ATE = 5	00 mg/kg	
13463-67-7	236-675-5	titanium dioxide	1 - < 5 %
	inhalation: LC	C50 = > 6.8  mg/l  (dusts or mists); oral:  LD50 = > 10000  mg/kg	·



Marston-Domsel GmbH

according to Regulation (EC) No 1907/2006

## MD-Mix Stahl/Metall, Alu, Wasser, Kupfer

Revision date: 17.04.2023 Product code: MIX Page 3 of 10

#### **Further Information**

titanium dioxide: Particle size: > 10 µm

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

When in doubt or if symptoms are observed, get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. If experiencing respiratory symptoms: Call a doctor.

#### After contact with skin

Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water. In case of skin reactions, consult a physician.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

### After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

## Suitable extinguishing media

Foam, Carbon dioxide (CO2), Dry extinguishing powder Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide Carbon dioxide (CO2))

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### **General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

#### For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.





according to Regulation (EC) No 1907/2006

## MD-Mix Stahl/Metall, Alu, Wasser, Kupfer

Revision date: 17.04.2023 Product code: MIX Page 4 of 10

#### For emergency responders

Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

#### 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains.

### For cleaning up

Take up mechanically, placing in appropriate containers for disposal. Treat the recovered material as prescribed in the section on waste disposal.

#### Other information

Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

### Advice on protection against fire and explosion

Usual measures for fire prevention.

## Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

#### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Hints on joint storage

Keep away from: Food and feedingstuffs

Protect from direct sunlight.

Do not store together with: Oxidizing agent

## Further information on storage conditions

Recommended storage temperature: 5 - 25°C

### 7.3. Specific end use(s)

Adhesives and sealants

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters



according to Regulation (EC) No 1907/2006

# MD-Mix Stahl/Metall, Alu, Wasser, Kupfer

Revision date: 17.04.2023 Product code: MIX Page 5 of 10

### **DNEL/DMEL values**

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
72244-98-5	Reaction products of pentaerythritol, propoxylated and 1	-chloro-2,3-epoxyprop	ane with hydrogen su	lfide
Worker DNEL,	, long-term	dermal	systemic	2,7 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	22 mg/m³
Consumer DNEL, long-term		inhalation	systemic	6,52 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	1,9 mg/kg bw/day
Consumer DN	EL, long-term	dermal	systemic	1,61 mg/kg bw/day

#### **PNEC** values

CAS No	Name of agent		
Environmenta	I compartment	Value	
72244-98-5 Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide			
Freshwater		0,07 mg/l	
Marine water		0,007 mg/l	
Freshwater sediment		0,322 mg/kg	
Marine sediment		0,032 mg/kg	
Micro-organisms in sewage treatment plants (STP)		10 mg/l	
Soil		0,023 mg/kg	

### Additional advice on limit values

To date, no national critical limit values exist.

### 8.2. Exposure controls









#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

### Individual protection measures, such as personal protective equipment

### Eye/face protection

Wear eye/face protection. (EN 166)

### Hand protection

Wear suitable gloves. (EN ISO 374)

By long-term hand contact

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material: > 0,4mm

Permeation time (maximum wear duration): > 480 min.

By short-term hand contact

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material: > 0,4mm

Permeation time (maximum wear duration): > 4800 min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the



according to Regulation (EC) No 1907/2006

## MD-Mix Stahl/Metall, Alu, Wasser, Kupfer

Revision date: 17.04.2023 Product code: MIX Page 6 of 10

specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

#### Thermal hazards

No information available.

### **Environmental exposure controls**

Avoid release to the environment.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: solid (Paste)
Colour: diverse
Odour: characteristic
Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not determined

boiling range:

Flammability: Non-flammable. Lower explosion limits: not determined Upper explosion limits: not determined Flash point: > 100 °C Auto-ignition temperature: not determined Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined Water solubility: not determined

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density:

Relative vapour density:

Particle characteristics:

not determined

1,9 - 2,09 g/cm³

not determined

not determined

not applicable

### 9.2. Other information

No information available.

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability


The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

## 10.4. Conditions to avoid

Protect against: Heat, Frost





according to Regulation (EC) No 1907/2006

## MD-Mix Stahl/Metall, Alu, Wasser, Kupfer

Revision date: 17.04.2023 Product code: MIX Page 7 of 10

#### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide Carbon dioxide (CO2))

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) 10020,0 mg/kg

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
72244-98-5	Reaction products of pe	Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide							
	oral	LD50 mg/kg	2600	Rat	Manufacturer				
	dermal	LD50 mg/kg	> 10200	Rabbit	Manufacturer				
90-72-2	72-2 2,4,6-tris(dimethylaminomethyl)phenol								
	oral	ATE	500 mg/kg						
13463-67-7	titanium dioxide								
	oral	LD50 mg/kg	> 10000	Rat	Manufacturer				
	inhalation (4 h) dust/mist	LC50	> 6,8 mg/l	Rat	Manufacturer				

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

May cause an allergic skin reaction. (bis-[4-(2,3-epoxipropoxi)phenyl]propane; Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide)

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## Information on likely routes of exposure

oral, dermal, inhalative, Eye contact

#### 11.2. Information on other hazards

### **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### **SECTION 12: Ecological information**



according to Regulation (EC) No 1907/2006

## MD-Mix Stahl/Metall, Alu, Wasser, Kupfer

Revision date: 17.04.2023 Product code: MIX Page 8 of 10

#### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
72244-98-5	Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide						
	Acute fish toxicity	LC50 8	7 mg/l	96 h	Danio rerio (zebrafish)	Manufacturer	
	Acute crustacea toxicity	EC50 1.	2 mg/l		Daphnia magna (Big water flea)	Manufacturer	

#### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

No information available.

#### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

Avoid release to the environment.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## List of Wastes Code - residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

## List of Wastes Code - contaminated packaging

150110

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

### **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.



according to Regulation (EC) No 1907/2006

### MD-Mix Stahl/Metall, Alu, Wasser, Kupfer

Revision date: 17.04.2023 Product code: MIX Page 9 of 10

14.4. Packing group: Inland waterways transport (ADN) No dangerous good in sense of this transport regulation.

14.1. UN number or ID number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es):

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

14.4. Packing group:

Marine transport (IMDG)

No dangerous good in sense of this transport regulation. 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

14.4. Packing group: Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: 14.2. UN proper shipping name:

14.3. Transport hazard class(es): 14.4. Packing group:

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

**ENVIRONMENTALLY HAZARDOUS:** No

14.6. Special precautions for user

No information available.

## 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to 2012/18/EU

Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

**National regulatory information** 

**Employment restrictions:** Observe restrictions to employment for juveniles according to the 'juvenile

> work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing

mothers.

Water hazard class (D): 2 - obviously hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

### Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service DNEL: Derived No Effect Level DMEL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration





according to Regulation (EC) No 1907/2006

## MD-Mix Stahl/Metall, Alu, Wasser, Kupfer

Revision date: 17.04.2023 Product code: MIX Page 10 of 10

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety

assessment, chapter R.20 (Table of terms and abbreviations).

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure			
Skin Irrit. 2; H315	Calculation method			
Eye Irrit. 2; H319	Calculation method			
Skin Sens. 1; H317	Calculation method			
Aquatic Chronic 3; H412	Calculation method			

### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
11047	May aguas an allargia

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

#### **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)