



SAFETY DATA SHEET

Diatex INFUTAC Aerosol

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Diatex INFUTAC Aerosol

REACH registration notes All chemicals used in this product have been registered under REACH where required.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

Uses advised against Flexible PVC due to the risk of plasticiser migration.

1.3. Details of the supplier of the safety data sheet

Supplier DIATEX S.A.S
 ZI LA MOUCHE
 58 RUE DES SOURCES
 69230 SAINT-GENIS-LAVAL
 Tél. standard : 04.78.86.85.00
 Henrique COSTA: hcosta@diatex.com

1.4. Emergency telephone number

Emergency telephone DIATEX 04.78.86.85.00 (Mon-Fri 09:00-17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)


Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Diatex INFUTAC Aerosol

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	METHYL ACETATE, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Supplementary precautionary statements	<p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p>

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria. In use may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS	30-60%
<0.1% 1,3 BUTADIENE	
CAS number: 68476-85-7	EC number: 270-704-2
Classification	
Flam. Gas 1 - H220	
Press. Gas (Liq.) - H280	
METHYL ACETATE	10-30%
CAS number: 79-20-9	EC number: 201-185-2
	REACH registration number: 01-2119459211-47-0012
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	

Diatex INFUTAC Aerosol

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	10-30%
CAS number: —	EC number: 921-024-6
	REACH registration number: 01-2119475514-35-XXXX
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments CAS 68476-85-7 - Petroleum Gas, The substance contains less than 0.1% w/w 1,3-butadiene, meaning that the full harmonised classification regarding Muta. 1B H340 and Carc. 1A H350 does not apply.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. If breathing stops, provide artificial respiration. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Get medical attention. Do not induce vomiting.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. If adhesive bonding occurs, do not force eyelids apart.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Coughing, chest tightness, feeling of chest pressure. Exposure may cause coughing or wheezing. In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death.
Ingestion	There may be soreness and redness of the mouth and throat.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	There may be irritation and redness. Eyes may water profusely.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Show this Safety Data Sheet to the medical personnel. Vapours may cause headache, fatigue, dizziness and nausea. Difficulty in breathing. Avoid breathing vapours.

Diatex INFUTAC Aerosol

Specific treatments If adhesive bonding occurs, do not force eyelids apart.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use alcohol-resistant foam, carbon dioxide or dry powder to extinguish.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous combustion products Oxides of carbon. Acrid smoke or fumes. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Do not breathe vapour. Avoid contact with eyes and prolonged skin contact.

For non-emergency personnel For the greatest protection, clothing should include anti-static overalls, boots and gloves. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke.

For emergency responders For the greatest protection, clothing should include anti-static overalls, boots and gloves.

6.2. Environmental precautions

Environmental precautions Contain spillage with sand, earth or other suitable non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Approach the spillage from upwind. Take precautionary measures against static discharge. Use only non-sparking tools.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 7 for information on safe handling. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Diatex INFUTAC Aerosol

Usage precautions	Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Wear protective clothing as described in Section 8 of this safety data sheet. Read and follow manufacturer's recommendations. Do not use in confined spaces without adequate ventilation and/or respirator. Do not eat, drink or smoke when using this product.
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas. Wash after use and before eating, smoking and using the toilet. Do not smoke in work area. Clean equipment and the work area every day.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Avoid contact with oxidising agents. Store away from the following materials: Alkalis. Protect from sunlight. Store in a cool and well-ventilated place.
Storage class	Extremely Flammable Aerosol

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
Usage description	Adhesive.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

METHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm 616 mg/m³

Short-term exposure limit (15-minute): WEL 250 ppm 770 mg/m³

WEL = Workplace Exposure Limit

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

DNEL

Consumer - Oral; Long term systemic effects: 699 mg/kg/day
 Workers - Oral; Long term systemic effects: 2035 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 699 mg/kg/day
 Workers - Dermal; Long term systemic effects: 773 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 608 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Observe any occupational exposure limits for the product or ingredients. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof electrical, ventilating and lighting equipment. Ensure operatives are trained to minimise exposure.

Personal protection

Wear protective work clothing.

Diatex INFUTAC Aerosol

Eye/face protection	Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.
Hand protection	To protect hands from chemicals, gloves should comply with European Standard EN374. (PE/PA/PE), 2.5mil (0.06mm), >480 min. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.
Other skin and body protection	Provide eyewash station. Avoid contact with skin. Wear suitable coveralls to prevent exposure to the skin.
Hygiene measures	Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Use appropriate hand lotion to prevent defatting and cracking of skin. Wash at the end of each work shift and before eating, smoking and using the toilet.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Short term Gas filter, type AX.
Thermal hazards	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
Environmental exposure controls	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Amber.
Odour	Hydrocarbons.
Odour threshold	Data lacking.
pH	pH (concentrated solution): 7
Melting point	Data lacking.
Initial boiling point and range	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane: 86-93°C @ 760 mm Hg Methyl acetate: 57°C @ 760 mm Hg
Flash point	A flash point method is not available but the major hazardous component, the Propellant has a flash point of <-60°C with flammability limits of 10.9% vol. upper and 1.4% vol. lower.
Evaporation rate	Not available.
Evaporation factor	Not available.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	Not available.

Diatex INFUTAC Aerosol

Other flammability	No specific test data are available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Liquid base: ~0.8 @ 20°C
Bulk density	Not applicable.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Liquid base: 50-250 cP @ 20°C
Explosive properties	In use may form flammable/explosive vapour-air mixture.
Explosive under the influence of a flame	Yes
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information	Not available.
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable under recommended transport or storage conditions.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended. Highly volatile.
------------------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Will not polymerise. In use may form flammable/explosive vapour-air mixture.
---	--

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Avoid the accumulation of vapours in low or confined areas.
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Strong acids. Strong oxidising agents. Strong alkalis.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Oxides of nitrogen. Oxides of carbon.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation

Skin corrosion/irritation	Irritating to skin.
----------------------------------	---------------------

Serious eye damage/irritation

Diatex INFUTAC Aerosol

Serious eye damage/irritation Causes eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anaesthetic effects and asphyxiation. Exposure may cause coughing or wheezing. May cause respiratory system irritation.

Ingestion

May cause nausea, headache, dizziness and intoxication.

Skin contact

Prolonged contact may cause redness, irritation and dry skin.

Eye contact

Irritating to eyes. There maybe irritation and redness. Eyes may water profusely

Acute and chronic health hazards

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Route of exposure

Inhalation Ingestion Skin absorption

Medical symptoms

Narcotic effect. Vapours may cause drowsiness and dizziness.

Toxicological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Toxicological effects Information given is based on product data, a knowledge of the components and the toxicology of similar products.

Acute toxicity - oral

Notes (oral LD₅₀) Not applicable.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not applicable.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ >20 mg/l, Inhalation, Rat

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Diatex INFUTAC Aerosol

Serious eye damage/irritation	Not irritating.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Not sensitising.
<u>Skin sensitisation</u>	
Skin sensitisation	Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	This substance has no evidence of mutagenic properties.
<u>Carcinogenicity</u>	
Carcinogenicity	Carcinogenicity in humans is not expected.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Does not contain any substances known to be toxic to reproduction.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	A single exposure may cause the following adverse effects: Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Not anticipated to present an aspiration hazard, based on chemical structure.
<u>Inhalation</u>	
Inhalation	May cause respiratory system irritation.
<u>Skin contact</u>	
Skin contact	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
<u>Route of exposure</u>	
Route of exposure	Inhalation Skin and/or eye contact

METHYL ACETATE

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 3705 mg/kg, Oral, Rabbit

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Acute toxicity - oral

Diatex INFUTAC Aerosol

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rabbit

Skin corrosion/irritation

Skin corrosion/irritation Skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Ecotoxicity Information given is based on product data, a knowledge of the components and the toxicology of similar products.

12.1. Toxicity

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Diatex INFUTAC Aerosol

Toxicity Not regarded as dangerous for the environment. The product is not believed to present a hazard due to its physical nature. Highly volatile.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , : 1-10 mg/l, Fish NOEC, : 1-10 mg/l, Fish
Acute toxicity - aquatic plants	LC ₅₀ , : 10-100 mg/l, Algae
Acute toxicity - microorganisms	LC ₅₀ , : 1-10 mg/l, Activated sludge NOEC, : 0.1-1 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Persistence and degradability The product is readily biodegradable.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Bioaccumulative potential Bioaccumulation is unlikely.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Bioaccumulative potential Not available.

12.4. Mobility in soil

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

Diatex INFUTAC Aerosol

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

Ecological information on ingredients.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Other adverse effects The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Ensure containers are empty before discarding (explosion risk). Dispose of contents/container in accordance with local regulations.

Disposal methods Do not puncture or incinerate, even when empty. Avoid the spillage or runoff entering drains, sewers or watercourses. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

Waste class Empty Aerosol: 15 01 10 (Containing hazardous residues), Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 04 (No hazardous residues).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Diatex INFUTAC Aerosol

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

IMDG Code segregation group SG69

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).
Health and Safety at Work etc. Act 1974 (as amended).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance Workplace Exposure Limits EH40.

Authorisations (Title VII Regulation 1907/2006) No specific authorisations are known for this product.

Restrictions (Title VIII Regulation 1907/2006) No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Classification procedures according to Regulation (EC) 1272/2008 Aerosol 1 - H222, H229: Weight of evidence. Skin Irrit. 2 - H315, Eye Irrit. 2 - H319, STOT SE 3 - H336, Aquatic Chronic 3 - H412: Calculation method.

Issued by Technical Department

Diatex INFUTAC Aerosol

Revision date	06/12/2018
Revision	1
SDS number	21563
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.