



Technical Data Sheet

Activator spray for Cyanoacrylates

Description

This product is an aerosol applied cyanoacrylate accelerant, which once applied to a difficult to bond substrate, significantly increases the cure speed of cyanoacrylate adhesive. The product is used primarily on wood mitre joints or on porous, acidic or difficult to bond surfaces.

Achieve an instant bond with no mess. Allow 10 seconds for positioning. Bonds to MDF, wood, chipboard, rubber, metals, most plastics, perspex, ceramics, aluminium and much more. Perfect for all cornice and profile mitres, trims, picture frames, MDF skirting and architrave joints, worktop end strips, PVCu trims and much more.

Technical Data

Consistency:	Liquid
Colour	Colourless
Specific gravity (DIN 53479)	Approx. 0.79 g/cm ³
VOC Level	605 g/l (grams/liter)
Solvent	<ul style="list-style-type: none">• LOW BOILING POINT MODIFIED NAPHTHA - NAPHTHA (PETROLEUM), SOLVENT-REFINED LIGHT• PROPANE• BUTANE• ISOBUTANE

Directions For Use

1. Ensure both surfaces to be bonded are clean, dry and free from grease.
2. Lightly spray one of the surfaces to be bonded with the activator.
3. Allow the activator to dry.
4. Apply a thin layer of the cyanoacrylate to the other surface.
5. Bring both surfaces together to achieve a bond. Depending on the substrates being used and temperature a rapid bond will be typically formed in 2-10 seconds.

Storage and Shelf Life

The activator should be stored between 5 and 30 degrees centigrade, away from direct sunlight. The aerosol has 12 months shelf life.

Health and Safety

Extremely flammable. Keep in well ventilated place away from sources of ignition. Do not breathe vapour or empty in drains. Do not pierce or burn after use.

**For further Health and Safety information - see separate MSDS sheet.*

Edition 05/2021, subject to change

All information, recommendations, and advice on the part of R&G Faserverbundwerkstoffe GmbH are published to the best of our knowledge and belief. They are noncommittal and contain neither explicit nor tacit assurance or warranty of particular properties. The values specified for properties are typical figures. Recommendations or advice serve to describe our products and possible applications in a general or exemplary, but not specifically individual manner. In the course of the constant technical advancement and improvement of our products there may be changes to the characteristic values, copy, and diagrams; no specific reference is made to any such change. Owing to our products' wide and highly diverse range of potential applications far beyond any of our attempts to analyse, the customer alone is responsible for examining our products' suitability for the respective processes and purposes and their respective processability. All and any protective rights and the applicable laws, terms, and conditions must be observed by the buyer or user of our products at their own responsibility. Publication is not a licence and does not intend the violation of any patents.