FILTER

Model: Prefilter 87 P2 NR

Cod.: WSB14052138

PRE Filter against dust, fumes and mists.
The pre filter must be used with the Sibol 87 range of filters and in conjunction with the RESPIR II, RESPIR II 2V and FIT MASK 87 half masks.

TECHNICAL INFORMATION

Respiratory resistance

Filter type	Class	Maximum resistance allowed (mbar)			
		15 l/min		47,5 l/min	
		Max standard	Measure	Max standard	Measure
P	2	0,7	< 0,7	2,4	< 2,4

Maximum filter penetration

Classification	Maximum penetration of test aerosols			
	Test with NaCl 47,5 l/min (%)		Test with parafin oil 47,5 l/min (%)	
P2	Max standard	Measure	Max standard	Measure
	6	<6	6	<6

Limitations of use

Do not use in environments with oxygen concentrations below 19.5%. The selection of the filter must be done considering the type of contaminant, the capacity of the filter, the leakage of the mask allowed by standard, TLV or TWA and the concentration in the workplace. The filter is marked NR, which indicates that it can be used for one work shift.

Classification

Filter in accordance with the provisions of Regulation (EU) 2016/425.
Class P2 filter for protection against particle penetration according to EN 143: 2000 + A1: 2006.

FILTER

Model: Prefilter 87 P2 NR
Cod.: WSB14052138

Marking

CE

Material

Body : filter material.
Box: PP

Storage

Store at a temperature between -5ºC y +35ºC with a maximum relative humidity of 75%.

Weight

6,5 g aprox

Dimensions / Packaging

Each filter is supplied with individual packaging with 2 hoops and 10 prefilters.

For more information please check the notes along with the products or the ones published on the website www.spasciani.com

NOTE: SPASCIANI SpA does not take any responsability for any possible and unintentional mistake and reserve the faculty of modify materials and technical characteristics of its products at any time and without any notice.