



## Technical Data Sheet

# Universal Colour Paste

- Base: styrene-free unsaturated polyester resin
- Highly concentrated
- Colourful
- Good to very good light resistance

<b>Technical / physical Data</b>	<b>Colour</b>	Colours on request
	<b>Viscosity on delivery</b>	flowable to pasty (dependend of pigment)
	<b>Density</b> theoretical determination	1.2 up to 2.2 g / m l + / - 0.1
<b>Shelf life</b>	At least 11 months in original containers, provided that the original containers are stored tightly closed at 15 to 25 °C. Opened containers are to be processed at short notice. The best before date of the respective batch is indicated on the product label. Storage beyond the specified period does not necessarily mean that the goods are unusable. In this case, however, it is essential to check the properties required for the respective application for reasons of quality assurance.	
<b>VProcessing and application</b>	<b>Processing</b>	in viscosity on delivery,
	<b>Addition</b>	2 up to 5 % colouring of resins, 10 up to 15 % colouring of top coat resins
	<b>Cleaning of tools</b>	Acetone
	<b>Notes on occupational health and safety</b> The usual precautionary measures for ventilation and personal protection during the handling of paints must be observed. Further information on hazardous substances, safety data and recommendations for health and environmental protection can be found in the corresponding safety data sheet.	
<b>Special instructions</b>	Perform preliminary tests. Pigments can delay or extend the the pot life depending on the colour shade.	
	<b>Test conditions</b> All statements are based on standard climate 20/65 DIN 50014.	
	These statements are based on our product knowledge and experience. We have no influence on the application itself. Please contact us for further information.	
	The information in this data sheet is a guide and does not represent a specification.	

All information, recommendations or advice given by R&G Faserverbundwerkstoffe GmbH are given to the best of our knowledge and belief. They are considered as non-binding information and contain neither explicit nor implicit assurances nor a guarantee of certain properties. The characteristic values given are typical values. Recommendations or advice describe our products and possible applications in a general or exemplary manner, but not in relation to individual cases. In the course of the continuous technical development and improvement of our products, changes may occur in the characteristic values, texts and graphics; no special reference is made to any possible change. The customer shall independently test our products with regard to their suitability for the intended processes and purposes and their corresponding processability, as the technical application possibilities of our products are numerous and vary greatly depending on the case. They are therefore beyond our control and are the sole responsibility of the customer. Any industrial property rights as well as existing laws and regulations are to be observed by the customer or user on his own responsibility. The publication is not a license and does not intend to infringe any patents.