

**GLASS FABRIC for PCB's**  
**PRODUCT SPECIFICATION**

<b>International Style</b>	<b>106</b>	<b>Old ITG description</b>	02034
<b>Style Number</b>	<b>00106</b>		
<b>Finish/Designation</b>	FE800		

		<b>Unit</b>	<b>Tolerance Specification</b>	
<b>Weave pattern</b>		Plain		ISO 9354
<b>Area weight</b>	g/m <sup>2</sup>	25,0	± 5%	DIN EN 12127
<b>Yarn</b>	tex			EN 12654-3
warp		EC5-5,5 tex		
weft		EC5-5,5 tex		
<b>Fibre count</b>	1/cm			DIN EN 1049
warp ends		22,0	± 5%	
weft picks		22,0	± 5%	

<b>Tensile strength</b>	N/cm			ASTM D 4029
warp		25		
weft		25		
<b>Finish content</b>	%	0,08 - 0,28		DIN ISO 1887
<b>Thickness (approx.)</b>	mm	0,030		ASTM 1777

<b>Remarks</b>
----------------

All statements herein are expressions of opinion which we believe to be accurate and reliable, but are presented without guarantee or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use in the infringement of any patent. No patent warranty of any kind, express or implied, is made or intended.  
Porcher Industries Germany GmbH, Benzstraße 14, D-89155 Erbach, Telefon +49 (0)7305 / 955-424, Fax +49 (0)7305 / 955-511