

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Hardener HT 2

Revision date: 23.11.2020

Product code: 105110

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Hardener HT 2

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Hardener (Crosslinker)

1.3. Details of the supplier of the safety data sheet

Company name:	R&G Faserverbundwerkstoffe GmbH	
	Composite Technology	
Street:	Im Meißel 7 - 13	
Place:	D-71111 Waldenbuch	
Post-office box:	1145	
	D-71107 Waldenbuch	
Telephone:	+49 (0)7157 5304-60	Telefax: +49 (0)7157 5304-70
e-mail:	info@r-g.de	
Contact person:	Michael Groß	Telephone: +49 (0)7157 5304-60
e-mail:	urlaubmg@r-g.de	
Internet:	www.r-g.de	
Responsible Department:	Management	

1.4. Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg
Tel: +49 (0)761 19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful if swallowed.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

3-aminomethyl-3,5,5-trimethylcyclohexylamine

benzyl alcohol

Phenol, styrenated

Signal word: Danger**Pictograms:**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Hardener HT 2

Revision date: 23.11.2020

Product code: 105110

Page 2 of 11

Hazard statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see ... on this label).
P330	Rinse mouth.
P331	Do NOT induce vomiting.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	25-50%
	220-666-8	612-067-00-9
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H312 H302 H314 H317 H412	
100-51-6	benzyl alcohol	25-50%
	202-859-9	603-057-00-5
	Acute Tox. 4, Acute Tox. 4; H332 H302	
61788-44-1	Phenol, styrenated	2,5-10%
	262-975-0	01-2119979575-18
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated clothing immediately.

After inhalation

consult a doctor.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Hardener HT 2

Revision date: 23.11.2020

Product code: 105110

Page 3 of 11

immediately all contaminated clothing and wash it before reuse. If skin irritation occurs.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Drink plenty of water and fresh air. Call a doctor immediately

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Extinguishing powder, Water spray jet.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

When heating up or in the fire case formation of poisonous gasses possible.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
Do not allow to enter the soil or subsoil.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Carefully cleaning scene of an accident.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate room ventilation, if necessary with vapour extraction at the workplace.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep/Store only in original container. Keep receptacles tightly sealed. Store in a dry place. 15 - 20 °C

Hints on joint storage

Store separately from foodstuffs.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Hardener HT 2

Revision date: 23.11.2020

Product code: 105110

Page 4 of 11

Further information on storage conditions

Keep receptacles tightly sealed.

7.3. Specific end use(s)

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.2. Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Recommended material: FKM (fluoro rubber), @0802.B008198

Thickness of glove material: > 0,5mm

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Combination filtering device (EN 14387) A-P2

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	light yellow
Odour:	like: Amines

pH-Value:	not determined	Test method
-----------	----------------	--------------------

Changes in the physical state

Melting point:	not determined
----------------	----------------

Initial boiling point and boiling range:	> 200 °C	DIN 53171
--	----------	-----------

Flash point:	> 100 °C	ISO 2719
--------------	----------	----------

Flammability

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Hardener HT 2

Revision date: 23.11.2020

Product code: 105110

Page 5 of 11

Solid: not applicable

Gas: not applicable

Lower explosion limits:

Upper explosion limits:

Auto-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature:

not determined

Oxidizing properties

Not oxidising.

Density (at 23 °C):

0,997 g/cm³ DIN 53217

Water solubility:

The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient:

not determined

Viscosity / dynamic:
(at 25 °C)

ca. 202 mPa·s ISO 9371

Vapour density:

not determined

Evaporation rate:

not determined

9.2. Other information

Solid content:

not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

In case of fire may be liberated: toxic and caustic gases and vapours

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Harmful if swallowed.

ATEmix calculated

ATE (oral) 1309,2 mg/kg; ATE (inhalation aerosol) 3,326 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Hardener HT 2

Revision date: 23.11.2020

Product code: 105110

Page 6 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	oral	LD50 mg/kg 1030	Rat	OECD 401	
	dermal	LD50 mg/kg 1840	Rabbit	Manufacturer	
	inhalation (4 h) aerosol	LC50 mg/l > 5,01	Rat	OECD 403	
100-51-6	benzyl alcohol				
	oral	LD50 mg/kg 1230	Rat	GESTIS	
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			
61788-44-1	Phenol, styrenated				
	oral	LD50 mg/kg 2197	Rat	Quantitative structure-activity relationship (QSAR)	
	dermal	LD50 mg/kg 3166	Rat	Quantitative structure-activity relationship (QSAR)	

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (3-aminomethyl-3,5,5-trimethylcyclohexylamine; Phenol, styrenated)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Hardener HT 2

Revision date: 23.11.2020

Product code: 105110

Page 7 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine					
	Acute fish toxicity	LC50 110 mg/l	96 h	Leuciscus idus (golden orfe)	Regulation (EC) No. 440/2008, Annex, C.1	
	Acute algae toxicity	ErC50 > 50 mg/l	72 h	Scenedesmus subspicatus	Regulation (EC) No. 440/2008, Annex, C.3	
	Acute crustacea toxicity	EC50 388 mg/l	48 h	Chaetogammarus marinus	IUCLID	
61788-44-1	Phenol, styrenated					
	Acute fish toxicity	LC50 4 mg/l	96 h	Pimephales promelas (fathead minnow)	Quantitative structure-activity relationship (QSAR)	
	Acute algae toxicity	ErC50 1,637 mg/l	72 h	Pseudokirchneriella subcapitata	Quantitative structure-activity relationship (QSAR)	
	Acute crustacea toxicity	EC50 1,878 mg/l	48 h	Daphnia magna	Quantitative structure-activity relationship (QSAR)	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	8 %	28	IUCLID
	Not readily biodegradable (according to OECD criteria)			
61788-44-1	Phenol, styrenated			
	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	73 %	14	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	0,8
100-51-6	benzyl alcohol	1,05

BCF

CAS No	Chemical name	BCF	Species	Source
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	3,16	Quantitative structure-activity relationship (QSAR)	IUCLID
61788-44-1	Phenol, styrenated	26,5	Carassius auratus (goldfish)	Quantitative structure-activity relationship (QSAR)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Hardener HT 2

Revision date: 23.11.2020

Product code: 105110

Page 8 of 11

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

List of Wastes Code - contaminated packaging

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN 2735
14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.(isophoronediamine)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8



Classification code: C7
Special Provisions: 274
Limited quantity: 5 L
Transport category: 3
Hazard No: 80
Tunnel restriction code: E

Other applicable information (land transport)

E1

Inland waterways transport (ADN)

14.1. UN number: UN 2735

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Hardener HT 2

Revision date: 23.11.2020

Product code: 105110

Page 9 of 11

14.2. UN proper shipping name: @27350111(isophoronediamine)

14.3. Transport hazard class(es): 8

14.4. Packing group: III

Hazard label: 8



Classification code: C7

Special Provisions: 274

Limited quantity: 5 L

Other applicable information (inland waterways transport)

E1

Marine transport (IMDG)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine)

14.3. Transport hazard class(es): 8

14.4. Packing group: III

Hazard label: 8



Marine pollutant: Nein

Special Provisions: 223, 274

Limited quantity: 5 L

EmS: F-A, S-B

Other applicable information (marine transport)

E1

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine)

14.3. Transport hazard class(es): 8

14.4. Packing group: III

Hazard label: 8



Special Provisions: A3 A803

Limited quantity Passenger: 1 L

IATA-packing instructions - Passenger: 852

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 856

IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E1

Passenger-LQ: Y841

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Hardener HT 2

Revision date: 23.11.2020

Product code: 105110

Page 10 of 11

Danger releasing substance: nonylphenol

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): 100 % (980 g/l)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H332 Harmful if inhaled.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Hardener HT 2

Revision date: 23.11.2020

Product code: 105110

Page 11 of 11

processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)