

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
  - **Trade name:** MEKP Härter FL 505 S
  - **1.2 Relevant identified uses of the substance or mixture and uses advised against** Not determined
  - **Application of the substance / the mixture** Hardening agent/ Curing agent
  - **1.3 Details of the supplier of the safety data sheet**
  - **Manufacturer/Supplier:**  
Vosschemie GmbH  
Esinger Steinweg 50  
D-25436 Uetersen  
Phone: +49 (0)4122 717 0; Fax: +49 (0)4122 717158; info@vosschemie.de
  - **Further information obtainable from:**  
Abteilung Labor / +49 (0)4122 717 0  
s.schaller@vosschemie.de
  - **1.4 Emergency telephone number:**  
Giftinformationszentrum (GIZ)-Nord, Goettingen, Deutschland  
Phone: +49 (0)551 19240
- 

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

Org. Perox. D H242 Heating may cause a fire.



GHS05 corrosion

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

Trade name: MEKP Härter FL 505 S

(Contd. of page 1)

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

STOT SE 3 H335 May cause respiratory irritation.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02

GHS05

GHS07

· **Signal word Danger**

· **Hazard-determining components of labelling:**

2-Butanone, peroxide

4-hydroxy-4-methylpentan-2-one

hydrogen peroxide

· **Hazard statements**

H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P234 Keep only in original container.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

Thermal decomposition with temperatures above 62 °C (SADT)

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

**Trade name: MEKP Härter FL 505 S**

(Contd. of page 2)

Risk of fire on contact with combustible substances or other substances effective in promoting the decomposition reaction.

Fire propagating effect due to oxygen release.

Pls. refer to section 10

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 131-11-3 EINECS: 205-011-6 Reg.nr.: 01-2119437229-36	dimethyl phthalate substance with a Community workplace exposure limit	25-50%
CAS: 1338-23-4 EC number: 700-954-4 Reg.nr.: 01-2119514691-43	2-Butanone, peroxide ⚠ Org. Perox. D, H242; ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	25-50%
CAS: 123-42-2 EINECS: 204-626-7 Reg.nr.: 01-2119473975-21	4-hydroxy-4-methylpentan-2-one ⚠ Flam. Liq. 3, H226; ⚠ Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	1.0-6.0%
CAS: 7722-84-1 EINECS: 231-765-0 Reg.nr.: 01-2119485845-22	hydrogen peroxide ⚠ Ox. Liq. 1, H271; ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412	1.0-4.0%
CAS: 102-82-9 EINECS: 203-058-7	tributylamine ⚠ Acute Tox. 2, H310; Acute Tox. 1, H330; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315	0.1-<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Immediately remove any clothing soiled by the product.

· **After inhalation:**

Remove person to fresh air and keep comfortable for breathing.

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

**Trade name: MEKP Härter FL 505 S**

(Contd. of page 3)

- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
Seek immediate medical advice.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. Then consult a doctor.  
Call a doctor immediately.
- **After swallowing:**  
Rinse mouth.  
Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.  
In case of fire, the product promotes combustion.  
May decompose explosively in absence of fire due to formation of vapour-air-mixture.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.
- **Additional information**  
Remove undamaged containers from the danger zone.  
Cool endangered receptacles with water spray.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Use suitable respiratory protective device in case of insufficient ventilation.  
Avoid contact with the eyes and skin.  
Keep away from ignition sources.  
Pls. refer to section 10
- **6.2 Environmental precautions:**  
Do not allow to enter sewers/ surface or ground water.  
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**  
Collect with an inert, non-combustible, absorbent material (i.e. sand, diatomaceous earth, acid binder, universal binder).  
Do not seal receptacle gas tight.  
Dispose of the material collected according to regulations.  
Pls. refer to section 10

(Contd. on page 5)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

**Trade name: MEKP Härter FL 505 S**

(Contd. of page 4)

**· 6.4 Reference to other sections***See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.***SECTION 7: Handling and storage****· 7.1 Precautions for safe handling***Keep receptacles tightly sealed.**Open and handle receptacle with care.**Do not return unused material to original containers – decomposition hazard!**Restrict the quantity stored at the work place.**Resistant to inert materials only.**Suitable materials: Stainless steel (DIN 1.4571), PVC, polyethylene, glass-lined apparatus.**Keep apart from dirt, rust, chemicals, especially reducing substances, acids, alkaline solutions, amines and heavy metal compounds (such as accelerator, desiccative, metal soaps). Avoid naked flames, sparks, other ignition sources and sunlight.**Avoid any direct contact with accelerators.**Weigh out and mix separately when processing polyester resins.**Avoid storage in containers with an airtight closure to prevent hazardous pressure build-up due to an eventual decomposition.**Avoid contact with the eyes and skin.**Ensure good ventilation/exhaustion at the workplace.**Do not inhale gases / fumes / aerosols.**Adhere to the workplace limit values and / or other threshold values.***· Information about fire - and explosion protection:***Protect from heat.**Protect from sunlight.**Prevent impact and friction.**Thermal decomposition with temperatures above 60°C under formation of explosive vapours/gases**Avoid naked flames, sparks, other ignition sources and sunlight.**Protect against electrostatic charges.**Anti-explosion protection required**Fumes can combine with air to form an explosive mixture.**Fire propagating effect due to oxygen release.**Keep apart from incompatible substances, dirt and high temperatures.**Pls. refer to section 10***· 7.2 Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:***Store in a cool location.**Store only in the original receptacle.**Prevent any seepage into the ground.**Adhere to the provisions of the Law on Water Protection.**Use only receptacles specifically permitted for this substance/product.***· Information about storage in one common storage facility:***Keep apart from other chemicals, in particular from accelerators.**Store away from foodstuffs.***· Further information about storage conditions:***Store in cool, dry conditions in well sealed receptacles.**Protect from heat and direct sunlight.*

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

**Trade name: MEKP Härter FL 505 S**

(Contd. of page 5)

- Protect from contamination.
- Store receptacle in a well ventilated area.
- Store under lock and key and out of the reach of children.
- **Recommended storage temperature:** -10 - < 30°C
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**131-11-3 dimethyl phthalate**

WEL (Great Britain)	Short-term value: 10 mg/m <sup>3</sup> Long-term value: 5 mg/m <sup>3</sup>
---------------------	--

**123-42-2 4-hydroxy-4-methylpentan-2-one**

WEL (Great Britain)	Short-term value: 362 mg/m <sup>3</sup> , 75 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm
---------------------	---

**78-93-3 butanone**

WEL (Great Britain)	Short-term value: 899 mg/m <sup>3</sup> , 300 ppm Long-term value: 600 mg/m <sup>3</sup> , 200 ppm Sk, BMGV
IOELV (EU)	Short-term value: 900 mg/m <sup>3</sup> , 300 ppm Long-term value: 600 mg/m <sup>3</sup> , 200 ppm

**7722-84-1 hydrogen peroxide**

WEL (Great Britain)	Short-term value: 2.8 mg/m <sup>3</sup> , 2 ppm Long-term value: 1.4 mg/m <sup>3</sup> , 1 ppm
---------------------	---

· **DNELs**

**131-11-3 dimethyl phthalate**

Oral	Long-term exposure - systemic effects	25 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	60 mg/kg bw/day (general population) 100 mg/kg bw/day (worker)
Inhalative	Long-term exposure - systemic effects	87 mg/m <sup>3</sup> (general population) 294 mg/m <sup>3</sup> (worker)

**1338-23-4 2-Butanone, peroxide**

Oral	Long-term exposure - systemic effects	0.75 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	1.5 mg/kg bw/day (general population) 3 mg/kg bw/day (worker)
Inhalative	Long-term exposure - systemic effects	1.125 mg/m <sup>3</sup> (general population) 5.288 mg/m <sup>3</sup> (worker)

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	Long-term exposure - systemic effects	3.4 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	3.4 mg/kg bw/day (general population) 9.4 mg/kg bw/day (worker)
Inhalative	Long-term exposure - systemic effects	11.8 mg/m <sup>3</sup> (general population)

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

**Trade name: MEKP Härter FL 505 S**

(Contd. of page 6)

	Acute/short-term exposure - local effects	66.4 mg/m <sup>3</sup> (worker) 120 mg/m <sup>3</sup> (general population)
	Long-term exposure - local effects	240 mg/m <sup>3</sup> (worker) 11.8 mg/m <sup>3</sup> (general population) 66.4 mg/m <sup>3</sup> (worker)

**7722-84-1 hydrogen peroxide**

Inhalative	Acute/short-term exposure - local effects	1.93 mg/m <sup>3</sup> (general population) 3 mg/m <sup>3</sup> (worker)
	Long-term exposure - local effects	0.21 mg/m <sup>3</sup> (general population) 1.4 mg/m <sup>3</sup> (worker)

**78-93-3 butanone**

Oral	Long-term exposure - systemic effects	31 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	412 mg/kg bw/day (general population) 1,161 mg/kg bw/day (worker)
Inhalative	Long-term exposure - systemic effects	106 mg/m <sup>3</sup> (general population) 600 mg/m <sup>3</sup> (worker)

**· PNECs**

**131-11-3 dimethyl phthalate**

PNEC aqua	192 mg/l (freshwater) 0.0192 mg/l (marine water)
PNEC sediment	1,403 mg/kg (freshwater)
PNEC STP	4 mg/l
PNEC soil	3.16 mg/kg (soil dw)

**1338-23-4 2-Butanone, peroxide**

PNEC aqua	0.0056 mg/l (freshwater) 0.00056 mg/l (marine water) 0.056 mg/l (intermittent releases)
PNEC sediment	0.0876 mg/kg (freshwater) 0.00876 mg/kg (marine water)
PNEC STP	1.2 mg/l

**123-42-2 4-hydroxy-4-methylpentan-2-one**

PNEC aqua	2 mg/l (freshwater) 0.2 mg/l (marine water)
PNEC sediment	9.06 mg/kg (freshwater) 0.91 mg/kg (marine water)
PNEC STP	82 mg/l
PNEC soil	0.63 mg/kg (soil dw)

**7722-84-1 hydrogen peroxide**

PNEC aqua	0.0126 mg/l (freshwater) 0.0126 mg/l (marine water) 0.0138 mg/l (intermittent releases)
PNEC sediment	47 mg/kg (freshwater)

(Contd. on page 8)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

Trade name: MEKP Härter FL 505 S

(Contd. of page 7)

PNEC STP	47 mg/kg (marine water)
PNEC soil	4.66 mg/l
	0.0023 mg/kg
<b>78-93-3 butanone</b>	
PNEC aqua	55.8 mg/l (freshwater)
	55.8 mg/l (marine water)
	55.8 mg/l (intermittent releases)
PNEC sediment	284.74 mg/kg (freshwater)
	284.7 mg/kg (marine water)
PNEC STP	709 mg/l
PNEC soil	22.5 mg/kg
PNEC oral	1,000 mg/kg

· **Ingredients with biological limit values:**

**78-93-3 butanone**

BMGV (Great Britain)	70 µmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Wash contaminated clothing before reuse.
- Avoid contact with the eyes and skin.
- Do not eat, drink, smoke or sniff while working.
- Use skin protection cream for skin protection.

· **Respiratory protection:**

- Ensure good ventilation/exhaustion at the workplace.
- Use suitable respiratory protective device in case of insufficient ventilation.
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Filter A/P2

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

(Contd. on page 9)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

Trade name: MEKP Härter FL 505 S

(Contd. of page 8)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Neoprene gloves

PVC gloves

Synthetic rubber gloves

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	Colourless
Odour:	Acrid

· **pH-value at 20 °C:** 4.7

· **Change in condition**

Melting point/freezing point: Undetermined.  
Initial boiling point and boiling range: Undetermined.

· **Flash point:** 55 °C (ISO 3679)

· **Ignition temperature:**

Decomposition temperature: 62 °C (SADT (25 kg))

· **Auto-ignition temperature:** Pls. refer to section 10

· **Explosive properties:** Pls. refer to section 10

· **Vapour pressure at 20 °C:** 20 hPa

· **Density at 20 °C:** ~ 1,1 g/cm<sup>3</sup>

· **Solubility in / Miscibility with water:** Partly miscible.

· **Partition coefficient: n-octanol/water:** Not determined

· **Viscosity:**

Dynamic at 20 °C: 16 mPas  
Kinematic: Not determined

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

Trade name: MEKP Härter FL 505 S

(Contd. of page 9)

· **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No decomposition if used according to specifications.
- **10.2 Chemical stability**  
No decomposition if used and stored according to specifications.  
Resistant to inert materials only.  
Suitable materials: Stainless steel (DIN 1.4571), PVC, polyethylene, glass-lined apparatus.
- **10.3 Possibility of hazardous reactions**  
Thermal decomposition or direct contact with numerous additives, such as reducing agents (i.e. amine accelerator), heavy metal compounds (in particular cobalt accelerators), acids and alkaline solutions, may lead to hazardous, autoaccelerating decomposition reactions, and possibly, to explosion or fire.
- **10.4 Conditions to avoid**  
Protect from heat.  
Avoid naked flames, sparks, other ignition sources and sunlight.  
To avoid thermal decomposition do not overheat.  
Thermal decomposition with temperatures above 62 °C (SADT)
- **10.5 Incompatible materials:**  
Keep apart from dirt, rust, chemicals, especially reducing substances, acids, alkaline solutions, amines and heavy metal compounds such as accelerator, desiccative, metal soaps)  
Avoid any direct contact with accelerators.
- **10.6 Hazardous decomposition products:**  
Formation of various organic degradation products and inflammable and explosive vapours/gases upon decomposition.  
Danger of forming toxic pyrolysis products.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**  
Harmful if swallowed or if inhaled.

· **LD/LC50 values relevant for classification:**

**131-11-3 dimethyl phthalate**

Oral	LD 50	>2,400 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50 /6h	9.3 mg/l

**1338-23-4 2-Butanone, peroxide**

Oral	LD50	1,017 mg/kg (rat) (OECD-401 (35-39% in DMP ))
Dermal	LD50	4,000 mg/kg (rabbit)

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	LD50	3,002 mg/kg (rat) (OECD 401)
Dermal	LD50	13,630 mg/kg (rab)
Inhalative	LD 50	>1,875 mg/kg (rat) (OECD 402)
	LC 50 / 4h	>7.6 mg/l (rat) (OECD 403)
	LC50 /4h	500-1,900 mg/m <sup>3</sup> (mouse)

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

**Trade name: MEKP Härter FL 505 S**

(Contd. of page 10)

**7722-84-1 hydrogen peroxide**

Oral	LD50	693.7 mg/kg (rat)
Inhalative	LC 50 / 4h	>0.17 mg/l (rat)

**78-93-3 butanone**

Oral	LD50	>2,193 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
Inhalative	LC50 /4h	34 mg/m <sup>3</sup> (rat)

**102-82-9 tributylamine**

Oral	LD50	420 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat) 190 mg/kg (rabbit) ((100%))
Inhalative	LC50 /4h	0.5 mg/l (rat) (OECD 403, vapour)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**  
Causes serious eye damage.

**· Subacute to chronic toxicity:**
**131-11-3 dimethyl phthalate**

Oral	NOAEL	1,000 mg/kg (rat) (bw/day, 24 month)
------	-------	--------------------------------------

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	NOAEL	300 mg/kg (rat) (6 weeks, liver, kidney)
Inhalative	NOAEL	1,041 mg/l (rat) (6 weeks, liver, kidney)
	LOAEL	0.48 mg/l (human)

- **Additional toxicological information:** May cause respiratory irritation.
- **Sensitisation** No sensitising effects known.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

**· Reproductive toxicity/Fertility**
**123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	NOAEL (fertility)	30-100 mg/kg (rat, parents) (OECD 422) 300 mg/kg (rat, F1) (OECD 422)
Inhalative	NOAEL (fertility)	4.1 mg/l (rat, parents) (OECD 416) 4.1 mg/l (rat, F1) (OECD 416)

**· Reproductive toxicity/Teratogenicity**
**131-11-3 dimethyl phthalate**

Oral	NOAEL (developmental toxicity)	3,570 mg/kg (rat) (OECD 414)
	NOAEL (maternally)	840 mg/kg (rat) (OECD 414)

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Inhalative	NOAEL (teratogenicity)	4.1 mg/l (rat) (OECD 414)
------------	------------------------	---------------------------

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation.

(Contd. on page 12)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

Trade name: MEKP Härter FL 505 S

(Contd. of page 11)

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### **131-11-3 dimethyl phthalate**

EC10/72h	193.09 mg/l ( <i>desmodesmus subspicatus</i> )
EC50/48h	33 mg/l ( <i>daphnia magna</i> )
EC50/72h	259.76 mg/l ( <i>desmodesmus subspicatus</i> )
EC50/96h	39.9 mg/l ( <i>algae</i> ) ( <i>Raphidocelis subcapitata</i> )
LC50/96h	50 mg/l ( <i>Lepomis macrochirus</i> )
	39 mg/l ( <i>pimephales promelas</i> )
NOEC	9.6 mg/l ( <i>daphnia magna</i> ) (21 d)
	11 mg/l ( <i>oncorhynchus mykiss</i> ) (102 d)

##### **1338-23-4 2-Butanone, peroxide**

EC50/48h	39 mg/l ( <i>daphnia magna</i> ) (OECD-202)
EC50/72h	5.6 mg/l ( <i>Pseudokirchneriella subcapitata</i> ) (OECD-201)
LC50/96h	44.2 mg/l ( <i>poecilia reticulata</i> ) (OECD-203)
NOEC	2.1 mg/l ( <i>Pseudokirchneriella subcapitata</i> )

##### **123-42-2 4-hydroxy-4-methylpentan-2-one**

EC50	9,016 mg/l ( <i>daphnia</i> ) (24h, OECD 203)
EC50/48h	>1,000 mg/l ( <i>daphnia magna</i> ) (OECD 202)
EC50/72h	>100 mg/l ( <i>Pseudokirchneriella subcapitata</i> ) (OECD 201)
EC50/0.5h	17 mg/l ( <i>activated slugde</i> )
LC50/96h	420 mg/l ( <i>Lepomis macrochirus</i> )
	>100 mg/l ( <i>Oryzias latipes</i> ) (OECD 203)
NOEC	100 mg/l ( <i>Pseudokirchneriella subcapitata</i> ) (OECD 201, 72h)
NOEC (aqua chron.)	>100 mg/l ( <i>daphnia magna</i> ) (21 d)
NOEL	825 mg/l ( <i>pseudomonas putida</i> )
TGK = toxicity threshold concentration	825 mg/l ( <i>pseudomonas putida</i> ) (16h, inhibition test)

##### **7722-84-1 hydrogen peroxide**

EC50/48h	2.4 mg/l ( <i>daphnia</i> )
EC50/72h	1.38 mg/l ( <i>Skeletonema costatum</i> )
LC50/96h	16.4 mg/l ( <i>pimephales promelas</i> )
NOEC	0.63 mg/l ( <i>daphnia magna</i> ) (21 d)
	0.63 mg/l ( <i>Skeletonema costatum</i> ) (72 h)

##### **78-93-3 butanone**

EC50/48h	308 mg/l ( <i>daphnia magna</i> )
LC50/96h	3,220 mg/l ( <i>Lepomis macrochirus</i> )
	2,993 mg/l ( <i>pimephales promelas</i> )

(Contd. on page 13)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

Trade name: MEKP Härter FL 505 S

(Contd. of page 12)

**102-82-9 tributylamine**

EC10/72h	1.4 mg/l ( <i>desmodesmus subspicatus</i> )
EC50/72h	1.4 mg/l ( <i>desmodesmus subspicatus</i> ) (DIN 38412)
LC50	>10 mg/l ( <i>danio rerio</i> ) (28 d)
	8 mg/l ( <i>daphnia magna</i> ) (48 h)
NOEC	315 mg/l ( <i>danio rerio</i> ) (28 d)

· **12.2 Persistence and degradability**

Easily biodegradable

**131-11-3 dimethyl phthalate**

Biodegradation 96-98 % (28d, OECD 301 E)

**1338-23-4 2-Butanone, peroxide**

Biodegradation 87 % (28 d (OECD- 301D))

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Biodegradation 98.51 % (OECD 301A, 28d)

**7722-84-1 hydrogen peroxide**

Biodegradation &gt;99 % (30 min)

· **12.3 Bioaccumulative potential****131-11-3 dimethyl phthalate**

log Kow 1.56 (OECD 107)

BCF 57 (*Lepomis macrochirus*) (21 day, OECD 305)**1338-23-4 2-Butanone, peroxide**

log Kow &lt;0.3 (OECD 117)

**123-42-2 4-hydroxy-4-methylpentan-2-one**

log Kow ≤0.09

BCF 0.5

**7722-84-1 hydrogen peroxide**

log Kow ≤1.57

**78-93-3 butanone**

log Kow 0.3

Kow 2

· **Behaviour in environmental systems:**· **12.4 Mobility in soil****131-11-3 dimethyl phthalate**

log Koc 1.57

**123-42-2 4-hydroxy-4-methylpentan-2-one**

log Koc 0.52

Koc 3.32

**78-93-3 butanone**

log Koc 0.6

Koc 3.8

· **Additional ecological information:**· **General notes:** Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 14)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

Trade name: MEKP Härter FL 505 S

(Contd. of page 13)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Disposal must be made according to official regulations.  
Dilute product with suitable inert liquid to a peroxide concentration below 10% and subsequently dispose of according to the refuse disposal act.
- **Waste disposal key:**  
The waste codes given above are to be considered recommendations; because of regional and industrial sector specific features, application of different waste codes is possible.

- **European waste catalogue**

16 05 06*	laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals
-----------	--

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- **14.1 UN-Number**  
· **ADR, IMDG, IATA** UN3105
  - **14.2 UN proper shipping name**  
· **ADR** 3105 ORGANIC PEROXIDE TYPE D, LIQUID (Methyl ethyl ketone peroxide)  
· **IMDG, IATA** ORGANIC PEROXIDE TYPE D, LIQUID (Methyl ethyl ketone peroxide)
  - **14.3 Transport hazard class(es)**  
· **ADR, IMDG, IATA**
- The image shows a yellow diamond-shaped hazard label with a red border and a black flame symbol in the center, representing Organic Peroxides (Class 5.2).
- **Class** 5.2 Organic peroxides.
  - **Label** 5.2
  - **14.4 Packing group**  
· **ADR** Void  
· **IMDG, IATA** II
  - **14.5 Environmental hazards:**  
· **Marine pollutant:** No
  - **14.6 Special precautions for user** Warning: Organic peroxides.

(Contd. on page 15)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

Trade name: MEKP Härter FL 505 S

(Contd. of page 14)

· EMS Number:	F-J,S-R
· Stowage Category	D
· Stowage Code	SW1 Protected from sources of heat.
· Segregation Code	SG35 Stow "separated from" acids. SG36 Stow "separated from" alkalis. SG72 See 7.2.6.3.2.

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR	
· Limited quantities (LQ)	125 ml
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

### SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H271 May cause fire or explosion; strong oxidiser.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 16)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.12.2017

V - 4

Revision: 13.12.2017

**Trade name: MEKP Härter FL 505 S**

(Contd. of page 15)

*H412 Harmful to aquatic life with long lasting effects.*

· **Department issuing SDS:** Abteilung Labor

· **Contact:** Frau S. Schaller

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*DNEL: Derived No-Effect Level (REACH)*

*PNEC: Predicted No-Effect Concentration (REACH)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Flam. Liq. 3: Flammable liquids – Category 3*

*Ox. Liq. 1: Oxidizing liquids – Category 1*

*Org. Perox. D: Organic peroxides – Type C/D*

*Acute Tox. 4: Acute toxicity – Category 4*

*Acute Tox. 2: Acute toxicity – Category 2*

*Acute Tox. 1: Acute toxicity – Category 1*

*Skin Corr. 1A: Skin corrosion/irritation – Category 1A*

*Skin Corr. 1B: Skin corrosion/irritation – Category 1B*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

· **\* Data compared to the previous version altered.**

GB