

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.02.2015

Version number 6

Revision: 25.02.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *presto finish spray putty*
- **Article number:** 165126, 308127, 483671
- **1.2 Relevant identified uses of the substance or mixture and uses advised against --**
- **Application of the substance / the mixture** Knife filler/ Surfacers
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MOTIP DUPLI GmbH
Kurt Vogelsang Strasse 6
D-74855 Haßmersheim
Tel.: +49/6266/75-0
msds@dupli-color.de
- **Further information obtainable from:** Abteilung Produktmanagement
- **1.4 Emergency telephone number:**
Tel.: +49 6266-75-310
Fax +49 6266-75-362
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.



Xi; Irritant

R38: Irritating to skin.



F+; Extremely flammable

R12: Extremely flammable.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.02.2015

Version number 6

Revision: 25.02.2015

Trade name: presto finish spray putty

(Contd. of page 1)

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene, mixture of isomers ☒ Xn R20/21; ☒ Xi R38 R10 ☒ Flam. Liq. 3, H226; ☒ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane ☒ F+ R12 ☒ Flam. Gas 1, H220; Press. Gas, H280	20-<25%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane ☒ F+ R12 ☒ Flam. Gas 1, H220; Press. Gas, H280	12.5-<20%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane ☒ F+ R12 ☒ Flam. Gas 1, H220; Press. Gas, H280	5-<10%
CAS: 546-93-0	Magnesite substance with a Community workplace exposure limit	2.5-<5.0%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.02.2015

Version number 6

Revision: 25.02.2015

Trade name: presto finish spray putty

(Contd. of page 2)

· **Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex I 67/548 EU), so the classification as carcinogen need not to apply.
For the wording of the listed risk phrases refer to section 16.

* **SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

* **SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, bluspoeder of waterstraal. Grotere brand met waterstraal of met schuim.
Vaten met water afkoelen.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3 Advice for firefighters -**

· **Protective equipment:** Mouth respiratory protective device.

* **SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Do not allow product to reach sewage system or any water course.

· **6.3 Methods and material for containment and cleaning up:**

Do not flush with water or aqueous cleansing agents

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* **SECTION 7: Handling and storage**

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.02.2015

Version number 6

Revision: 25.02.2015

Trade name: presto finish spray putty

(Contd. of page 3)

- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** 2B
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene, mixture of isomers

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

546-93-0 Magnesite

WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust
-----	---

- **Ingredients with biological limit values:**

1330-20-7 xylene, mixture of isomers

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

- **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
Not necessary if room is well-ventilated.
Otherwise, filter class A / P2 or self contained.

(Contd. on page 5)

GB

Trade name: presto finish spray putty

(Contd. of page 4)

· **Protection of hands:**



Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Butyl rubber, BR

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

· **Eye protection:** Safety glasses

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 365 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower: 1.1 Vol %

Upper: 10.9 Vol %

· **Vapour pressure at 20 °C:** 8300 hPa

· **Density at 20 °C:** 0.92 g/cm³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.02.2015

Version number 6

Revision: 25.02.2015

Trade name: presto finish spray putty

(Contd. of page 5)

- | | |
|---|--|
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| VOC-(EU) | --- |
| | 663.9 g/l |
| · VOC-EU% | 72.15 % |
| · Solids content: | 29.3 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

1330-20-7 xylene, mixture of isomers

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	6350 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitizing effect by skin contact is possible by prolonged exposure.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

Vapours have narcotic effect.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

1330-20-7 xylene, mixture of isomers

EC50 (24h)	>175 mg/l (bacteria)
EC50 / 48h	3.82 mg/l (daphnia magna / Wasserfloh)
EC50/72h	4.7 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	7.6 mg/l (oncorhynchus mykiss / Regenbogenforelle)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.02.2015

Version number 6

Revision: 25.02.2015

Trade name: presto finish spray putty

(Contd. of page 6)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging
15 01 11*	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** UN1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 2 5F Gases.
- **Label** 2.1

- **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.02.2015

Version number 6

Revision: 25.02.2015

Trade name: presto finish spray putty

(Contd. of page 7)

· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Gases. - F-D,S-U
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	IL Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	IL Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H220 Extremely flammable gas.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
- **R10 Flammable.**
- **R12 Extremely flammable.**
- **R20/21 Harmful by inhalation and in contact with skin.**
- **R38 Irritating to skin.**
- **Contact:** Anwendungstechnik
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.02.2015

Version number 6

Revision: 25.02.2015

Trade name: presto finish spray putty

(Contd. of page 8)

IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Gas 1: Flammable gases, Hazard Category 1
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
Press. Gas: Gases under pressure: Compressed gas
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

GB